Form 3160-5 (November 1983) (Formerly 9-331)

UNITED STATES

SUBMIT IN TRIPLICA (Other Instructions on reverse side) Budget Bureau No. 1004-0135 Expires August 31, 1985 15/

DEPARTMENT OF THE INTERIORM. Oil Cons. Division 5. LEASE DESIGNATION AND SERIAL NO. LC-029419-B 6. IF INDIAN, ALLOTTEE OR TRIBE NAME SUNDRY NOTICES AND REPORTS (Do not use this form for proposals to drill or to deepen or plug back to 2446 pm Nurv 88210-2834 Use "APPLICATION FOR PERMIT - " for such proposals.) 7. UNIT AGREEMENT NAME OTHER OIL GAS Skelly Unit WELL. WELL. 8. API WELL NO. NAME OF OPERATOR §30-015-29184 The Wiser Oil Company 9. WELL NO. ADDRESS OF OPERATOR 263 P. O. Box 2568 Hobbs, New Mexico 88241 10. FIELD AND POOL, OR WILDCAT LOCATION OF WELL (Report location clearly and in accordance with any State requirements.) See also space 17 below.) Grayburg Jackson 7-Rivers 15' FNL & 1262' FWL At surface 11.7SEC., T., R., M., OR BLK. AND Sec. 27-T17S-R31E SURVEY OR AREA Unit D Sec. 27-T17S-R31E 12. COUNTY OR PARISH 14. PERMIT NO 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 13. STATE Eddv NM Check Appropriate Box to indicate Nature of Notice, Report, or Other Data 16. SUBSEQUENT REPORT OF: NOTICE OF INTENTION TO: PULL OR ALTER CASING WATER SHUT-OFF REPAIRING WELL TEST WATER SHUT OFF FRACTURE TREAT MULTIPLE COMPLETE FRACTURE TREATMENT ALTERING CASING SHOOT OR ACIDIZE SHOOTING OR ACIDIZING ABANDONMENT * ABANDON* (Other) Spudding, Cementing Surface & Production Casin CHANGE PLANS REPAIR WELL (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) (Other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS: (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) MIRU Norton Drilling Co., Rig #5. Spudded 12-1/4" surface hole @ 12:15 p.m., 10/16/96. Drilled hole to 445'. Ran 10 its. 8-5/8", 23#, ISW-42 ST& C csg. Set at 443'. Halliburton cemented with 325 sx. Class "C" containing 1/4#/sk. Flocele + 2% CaCl. Plug down @ 9:30 p.m., 10/16/96. Circulated 68 sx. cmt. Had water flow f/2820'-3900' T.D. BLM was notified, no representative present. NU BOP & tested csg. to 1000# for 30 minutes, no pressure loss. WOC 12 hrs. Drilled 7-7/8" production hole to a depth of 3900'. Ran casing as follows: Ran 93 jts. 5-1/2" 17#, J-55, LT&C csg. Set at 3900'. Halliburton cemented w/1000 gals. Superflush 102 + 1050 sx. Halliburton Lite + 8# salt/sk. + 1/4# Flocele/sk. followed by 250 sx. Premium Plus w/3#KCL/sk. + .5% Halad 344 + 1/4# Flocele/sk. Displaced w/l bbl. FW + 12 bbls. MSA + 77 bbls. FW w/Lo-Surf 300. Plug down at 12:15 p.m. 10/21/96. Circ. 111 sx. cmt. Pressure tested casing to 1500# for 30 minutes, no pressure loss. Released rig at 2:15 p.m. 10/21/96. BLM was notified, no representative present. 18 Thereby certify that the foregoing is true and correct. TITLE Drilling Department DATE October 22, 1996 (This space for Federal or State office use) APPROVED BY CONDITIONS OF APPROVAL, IF ANY: *See Instruction On Reverse Side Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fibitious or fraudulent statements or representations as to any matter within its jurisdiction.