Form 3160-5 (November 1983) (Formerly 9-331)

## **UNITED STATES**

SUBMIT IN TRIPLICATE \* (Other Instructions on

Budget Bureau No. 1004-0135 Expires August 31, 1985

DEPARTMENT OF THE INTERIOR  RUBEAU OF LAND MANAGEMENT	5. LEASE DESIGNATION AND SERIAL NO. LC-029420-B
SUNDRY NOTICES AND REPORTS ON WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
(Do not use this form for proposals to drill or to deepen or plug backets a different reservoir. Division	

	CES AND REPORT  osals to drill or to deepen or plug  ATION FOR PERMIT - " for suc	TS ON WELLS  THE REPORT OF THE PROPERTY OF THE	6. IF INDIAN, ALLOTTEE OR TRIE	BE NAME
1	THE	811 S. 1st Street Artesia, NM 88210-2834	7. UNIT AGREEMENT NAME Skelly Unit	
2 NAME OF OPERATOR The Wiser Oil Company			8. API WELL NO. 30-015-29210 9. WELL NO.	
3 ADDRESS OF OPERATOR P. O. Box 2568 Hobbs, N			274  10. FIELD AND POOL, OR WILDCA	A'T
4. LOCATION OF WELL (Report location See also space 17 below.) At surface 1443' FNI Sec. 28-T1 Unit G	& 1462' FEL	<b>0EC 03 '9</b> o. c. d.	Grayburg Jackson 7-Rive 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 28-T17S-R31E	
14. PERMIT NO	15. ELEVATIONS (Show wheth 3801'	her DF, RT, GR, etc.)	12. COUNTY OR PARISH  Eddy	13. STATE NM
6. Check A  NOTICE OF INTE	-	e Nature of Notice, Report, or Othe		· · · · · · · · · · · · · · · · · · ·
TEST WATER SHUT OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL	PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON* CHANGE PLANS	(Note: Report results of	nting Surface & Production Ca	sing
Completion or Recompletion Report and Log form.)  7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS: (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)  MIRU Norton Drilling Co., Rig #7. Spudded 12-1/4" surface hole @ 5:00 p.m., 11/10/96. Drilled hole to 444'. Ran 10 jts. 8-5/8", 20#, ISW-42 ST& C csg. Set at 442'. Halliburton cemented with 325 sx. Class "C" containing 1/4#/sk. Flocele + 2% CaCl. Plug down @ 6:00 a.m., 11/11/96. Circulated 34 sx. cmt. BLM was notified, no representative present. NU BOP & tested csg. to 1000# for 30 minutes, no pressure loss. WOC 12 hrs.  Drilled 7-7/8" production hole to a depth of 3950'. Ran casing as follows: Ran 95 jts. 5-1/2" 17#, J-55, LT&C csg. Set at 3950'. Halliburton cemented w/1000 gals. Superflush 102 + 900 sx. Halliburton Lite + 8# salt/sk. + 1/4# Flocele/sk. followed by 250 sxs. Premium Plus w/3#KCL/sk. + .5% Halad 344 + 1/4# Flocele/sk. Displaced w/l bbl. FW + 12 bbls. MSA + 78 bbls. FW w/Lo-Surf 300. Plug down at 12:45 a.m. 11/16/96. Circ. 118 sx. cmt. Pressure tested casing to 1500# for 30 minutes, no pressure loss. Released rig at 2:45 a.m. 11/16/96. BLM was notified, no representative present.				
8 Thereby certify that the foregoing is true and SIGNED Mary Je Junio		illing Department	DATE November 19	1996
				<del></del>

(This space for Federal or State office use) APPROVED BY TITLE \*See Instruction On Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, and tious of fraudulent statements or representations as to any matter within its jurisdiction. CONDITIONS OF APPROVAL, IF ANY: