

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993
Designation and Serial No.

DEC 3 9 42 AM '96

NM-0437524

Indian, Allottee or Tribe Name

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

NM Oil Cons. Division

811 S. 1st Street

SUBMIT IN TRIPLICATE

Artesia, NM 88210-2834

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

DEC 13 '96

2. Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1471 O. C. D.

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1650' FSL & 990' FEL of Section 15-T18S-R29E (Unit I, NESE)

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Cerros AQF Federal #1

9. API Well No.

30-015-29276

10. Field and Pool, or Exploratory Area

Cedar Lake Morrow

11. County or Parish, State

Eddy Co., NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Spud, resume drilling,
surface casing & cement

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded a 26" hole with rat hole machine at 12:00 noon 11-22-96. Set 80' of 20" conductor pipe. Cemented to surface. NOTE: Notified Don Early w/BLM-Carlsbad of spud. Resumed drilling a 17-1/2" hole with rotary tools at 12:45 AM 11-24-96.

TD 468'. Reached TD at 10:45 AM 11-24-96. Ran 11 joints of 13-3/8" 54.5# J-55 (473.70') of casing set at 468'. 1-Texas Pattern notched guide shoe set at 468'. Insert float set at 425'. Cemented with 100 sacks Class "H" (Thixad), 10% gypsum, 10#/sack gilsonite, 1/4#/sack celloflake and 1% CaCl2 (yield 1.52, weight 14.6) and 225 sacks Class "C" (65-35-6), 6% gel, 5#/sack gilsonite and 2% CaCl2 (yield 1.93, weight 12.6). Tailed in with 200 sacks Class C 2% CaCl2 (yield 1.34, weight 14.8). PD 4:30 PM 11-24-96. Bumped plug to 700 psi, OK. Circulated 216 sacks to pit. WOC. Nippled up and tested to 1000 psi for 30 minutes, OK. Cut off and welded on flow nipple. Drilled out at 12:30 PM 11-25-96. WOC 20 hours. Reduced hole to 12-1/4". Resumed drilling.

AS

14. I hereby certify that the foregoing is true and correct

Signed

Rusty Klein

Title Operations Technician

Date Nov. 29, 1996

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date