Form 3160-5 (November 1983) (Formerly 9-331)

(This space for Federal or State office use)

CONDITIONS OF APPROVAL, IF ANY:

APPROVED BY

UNITED . . ATES DEPARTMENT OF THE INTERIOR

SUBMIT IN TRIPLICATE - OIBGONS reau No. 1004-0135 (Other Instructions on M. DI Warding of 31, 1985 015/

reverse sit 301 W. Carabach Avenue serial no BUREAU OF LAND MANAGEMENT Artesiac NM 2088210 NM 6. IF INDIAN, ALLOTTEE OR TRIBE NAME SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT - " for such proposals.) 7. UNIT AGREEMENT NAME 1 Skelly Unit OTHER OIL GAS WELL WELL. 8. WELL NAME AND NO. 2. NAME OF OPERATOR 284-Y The Wiser Oil Company 9. API WELL NO. ADDRESS OF OPERATOR 30-015-29314 P.O. Box 2568 Hobbs, New Mexico 88241 10. FIELD AND POOL, OR WILDCAT LOCATION OF WELL (Report location clearly and in accordance with any State requirements. Grayburg Jackson Seven Rivers See also space 17 below.) 11. SEC., T., R., M., OR BLK. AND At surface SURVEY OR AREA 2586' FSL & 2535' FEL Sec. 28-T17S-R31E Unit J 13. STATE 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 12. COUNTY OR PARISH 14. PERMIT NO NM Eddy County 3763 Check Appropriate Box to indicate Nature of Notice, Report, or Other Data 16. SUBSEQUENT REPORT OF: NOTICE OF INTENTION TO: REPAIRING WELL PULL OR ALTER CASING WATER SHUT-OFF TEST WATER SHUT OFF ALTERING CASING FRACTURE TREATMENT MULTIPLE COMPLETE FRACTURE TREAT ABANDONMENT * SHOOTING OR ACIDIZING SHOOT OR ACIDIZE ABANDON* (Other) Frac Grayburg CHANGE PLANS REPAIR WELL (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS: (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) 12/10/97 MIRU Cobra Well Service. POH w/rods & pump. NU BOP. LD 2-7/8" tbg. HES set 5-1/2" Howco RBP @ 3550'. ND BOP & WH. Install frac valve. RD unit. HES frac'd Upper Grayburg f/3472'-3536' w/500 gals. 15% NE-FE acid flushed w/82 bbls. fresh water, 9500 gals. gelled water, 15,500 gals. 20# Delta frac & 36,000# 16/30 brown sand. ATP 2830# @ 25 bpm. MTP 3100# @ 26.5 bpm. ISIP 247#. 5 min. 2226#. 10 min. 2118#. 15 min. 1960#. 12/29/97MIRU Lucky Well Service. Removed frac valve. NU BOP & enviro-vat. 12/30/97 RIH w/Howco retr. head on 2-7/8" tbg. Cleaned out sand f/3530'-3550'. POH w/RBP. RIH w/2-7/8" tbg. Set TAC @ 3370' w/10,000# tension. ND BOP. Installed ACCEPTED FOR RECORD 12/31/97 RIH w/rods. Left well pumping to battery. RDMO. ALEXIS C. SWOBODA ETROLEUM ENGINEE 18. I hereby certify that the foregoing is true and correct. DATE __August 18, 2001 TITLE Production Tech II

*See Instruction On Reverse Side