

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO.
30-015-29375

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

7. Lease Name or Unit Agreement Name
Scanlon Draw "34" State

1. Type of Well:

OIL WELL ☐ GAS WELL ☒ OTHER

2. Name of Operator

Mewbourne Oil Company

8. Well No.

1

3. Address of Operator

P.O. Box 5270, Hobbs, NM 88241

9. Pool name or Wildcat

North Turkey Track Morrow

4. Well Location

Unit Letter 0 : 660 Feet From The South Line and 1650 Feet From The East Line

Section 34 Township 18S Range 28E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3524 GL

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Spud & Surface Casing Cement ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 12 1/4" intermediate hole to 3003' K.B. Ran 19 jts 8 5/8" 32# K-55 ST&C LS plus 49 jts 8 5/8" 24# J-55 ST&C and set @ 3003'. BJ cemented as follows:
Lead - 1000 sks ("C" + poz) 35:65:6 + 10#/sk gilsonite + 1/4#/sk Cello flake, mixed at 12.52 #/gal, 1.95 ft/sk and 9.60 gal/sk. Tail - 200 sks "C" + 1% CaCl₂ mixed at 14.80 #/gal, 1.33 ft/sk and 6.33 gal/sk. Displaced with 186 bbls fresh water. PP 100-875 psi. Bumped plug to 1500 psi at 9:30 am 3/14/97. Float held OK. Had full returns throughout job. Circulated 115 sks cement to pit. State representative was not present. Cut-off 8 5/8" and set B-section, test to 1500#, held good.

WOC has?

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Robert A. Jones TITLE Drilling Engineer DATE 3/24/97

TYPE OR PRINT NAME Robert A. Jones TELEPHONE NO. 393-5905

(This space for State Use) ORIGINAL SIGNED BY TIM W. GUM
DISTRICT SUPERVISOR

APPROVED BY _____ TITLE _____ DATE MAR 28 1998

CONDITIONS OF APPROVAL, IF ANY: