Form 3160-5 (June 1990)

UNITED STATES DEPARTME! OF THE INTERIOR BUREAU OF LAND MANAGEMENT

SIC

FORM APPROVED Budget Bureau No. 1004-0135

SUNDRY NOTICES A		25 3 Expires March 31, 1993
	ND REPORTS ON WELLS	Lease Designation and Serial No.
Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.		NINA 005004
Onot use this form for proposals to drill of to	PERMIT—" for such proposals	NM-025604 6. If Indian, Allottee or Tribe Name
USE APPLICATION FOR	PENMIT— Tot such proposats	6. It fildian, Another of Tribe Name
SUBMIT IN	TRIPLICATE	NA
	Q. 45	7. If Unit or CA, Agreement Designation
Type of Well	con 4 4 1337	1
⊠ Oil Gas Well Other	\$137 + 10 Appl	NA N
2. Name of Operator		8. Well Name and No.
DEVON ENERGY CORPORATION (NEVADA	A)	Hawk "9!" Federal #13
3. Address and Telephone No.		9. API Well No.
	HOMA CITY, OKLAHOMA 73102 (405) 235-3611	20 015 20515
		30-015-29515 10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Desc	cription)	
2310' FSL & 790' FEL of Section 9-18S-27E; "H"		Red Lake (Q-GB-SA)
		11. County or Parish, State
		Eddy County, NM
ALIENY ADDRODDIATE DOVAN	O INDICATE MATURE OF NOTICE BE	DODE OF OTHER DATA
CHECK APPROPRIATE BUX(S) 1	O INDICATE NATURE OF NOTICE, REF	
TYPE OF SUBMISSION	TYPE OF ACTION	· · · · · · · · · · · · · · · · · · ·
Notice of Intent .	Abandonment	Change of Plans
Notice of intent .	Recompletion	New Construction
Subsequent Report	Plugging Back	Non-Routine Fracturing
Subsequent Report	Casing Repair	Water Shut-Off
D. S. Albandanana Nation	Altering Casing	Conversion to Injection
Final Abandonment Notice	Other spud, csg strings & TD.	Dispose Water
	Other spud, esg sumgs & 1D.	(Note: Report results of multiple completion on Well
· · · · · · · · · · · · · · · · · · ·		
	the state of the s	Completion or Recompletion Report and Log form.)
Describe Proposed or Completed Operations (Clearly state all perticularly subsurface locations and measured and true vertical depths for a	ment details, and give pertinent dates, including estimated date of starting	
subsurface locations and measured and true vertical depths for a	all markers and zones pertinent to this work.)*	any proposed work. If well is directionally drilled, give
subsurface locations and measured and true vertical depths for a	all markers and zones pertinent to this work.)*	any proposed work. If well is directionally drilled, give
subsurface locations and measured and true vertical depths for a Spudded this well on 7/26/97 at 0730 hr	rs and drld a 12 1/4" hole to 1191'. On 5/2	any proposed work. If well is directionally drilled, give
subsurface locations and measured and true vertical depths for a Spudded this well on 7/26/97 at 0730 hr	all markers and zones pertinent to this work.)*	any proposed work. If well is directionally drilled, give 27/97 ran 30 jts 8 5/8" 24# J-55
subsurface locations and measured and true vertical depths for a Spudded this well on 7/26/97 at 0730 hr	rs and drld a 12 1/4" hole to 1191'. On 5/2	any proposed work. If well is directionally drilled, give 27/97 ran 30 jts 8 5/8" 24# J-55
Spudded this well on 7/26/97 at 0730 hr ST&C csg, set at 1190'. Cemented w/3	rs and drld a 12 1/4" hole to 1191'. On 5/2 350 sxs lite "C" & 200 sxs lite "C". Circ'	any proposed work. If well is directionally drilled, give 27/97 ran 30 jts 8 5/8" 24# J-55 d 51 sxs cmt.
Spudded this well on 7/26/97 at 0730 hr ST&C csg, set at 1190'. Cemented w/3 Drld 7 7/8" hole and reached TD 2650'	rs and drld a 12 1/4" hole to 1191'. On 5/2 350 sxs lite "C" & 200 sxs lite "C". Circ' on 8/9/97 at 0200 hrs. Schlumberger ran	any proposed work. If well is directionally drilled, give 27/97 ran 30 jts 8 5/8" 24# J-55 d 51 sxs cmt. LDT/CNL/DLL/MSFL/GR logs.
Spudded this well on 7/26/97 at 0730 hr ST&C csg, set at 1190'. Cemented w/3 Drld 7 7/8" hole and reached TD 2650'	rs and drld a 12 1/4" hole to 1191'. On 5/2 350 sxs lite "C" & 200 sxs lite "C". Circ'	any proposed work. If well is directionally drilled, give 27/97 ran 30 jts 8 5/8" 24# J-55 d 51 sxs cmt. LDT/CNL/DLL/MSFL/GR logs. C" + 275 sx Class "C". Circ'd 95
Spudded this well on 7/26/97 at 0730 hr ST&C csg, set at 1190'. Cemented w/3 Drld 7 7/8" hole and reached TD 2650'	rs and drld a 12 1/4" hole to 1191'. On 5/2 350 sxs lite "C" & 200 sxs lite "C". Circ' on 8/9/97 at 0200 hrs. Schlumberger ran	any proposed work. If well is directionally drilled, give 27/97 ran 30 jts 8 5/8" 24# J-55 d 51 sxs cmt. LDT/CNL/DLL/MSFL/GR logs. C" + 275 sx Class "C". Circ'd 95
Spudded this well on 7/26/97 at 0730 hr ST&C csg, set at 1190'. Cemented w/3 Drld 7 7/8" hole and reached TD 2650' Ran 60 jts 5 1/2" 15.5# J-55 LT&C csg	rs and drld a 12 1/4" hole to 1191'. On 5/2 350 sxs lite "C" & 200 sxs lite "C". Circ' on 8/9/97 at 0200 hrs. Schlumberger ran	any proposed work. If well is directionally drilled, give 27/97 ran 30 jts 8 5/8" 24# J-55 d 51 sxs cmt. LDT/CNL/DLL/MSFL/GR logs. C" + 275 sx Class "C". Circ'd 95
Spudded this well on 7/26/97 at 0730 hr ST&C csg, set at 1190'. Cemented w/3 Drld 7 7/8" hole and reached TD 2650' Ran 60 jts 5 1/2" 15.5# J-55 LT&C csg sxs cmt.	rs and drld a 12 1/4" hole to 1191'. On 5/2 350 sxs lite "C" & 200 sxs lite "C". Circ' on 8/9/97 at 0200 hrs. Schlumberger rang, set at 2649'. Cemented w/250 sx lite "C".	any proposed work. If well is directionally drilled, give 27/97 ran 30 jts 8 5/8" 24# J-55 d 51 sxs cmt. LDT/CNL/DLL/MSFL/GR logs. C" + 275 sx Class "C". Circ'd 95
Spudded this well on 7/26/97 at 0730 hr ST&C csg, set at 1190'. Cemented w/3 Drld 7 7/8" hole and reached TD 2650' Ran 60 jts 5 1/2" 15.5# J-55 LT&C csg	rs and drld a 12 1/4" hole to 1191'. On 5/2 350 sxs lite "C" & 200 sxs lite "C". Circ' on 8/9/97 at 0200 hrs. Schlumberger rang, set at 2649'. Cemented w/250 sx lite "C".	any proposed work. If well is directionally drilled, give 27/97 ran 30 jts 8 5/8" 24# J-55 d 51 sxs cmt. LDT/CNL/DLL/MSFL/GR logs. C" + 275 sx Class "C". Circ'd 95
Spudded this well on 7/26/97 at 0730 hr ST&C csg, set at 1190'. Cemented w/3 Drld 7 7/8" hole and reached TD 2650' Ran 60 jts 5 1/2" 15.5# J-55 LT&C csg sxs cmt.	rs and drld a 12 1/4" hole to 1191'. On 5/2 350 sxs lite "C" & 200 sxs lite "C". Circ' on 8/9/97 at 0200 hrs. Schlumberger rang, set at 2649'. Cemented w/250 sx lite "C".	any proposed work. If well is directionally drilled, give 27/97 ran 30 jts 8 5/8" 24# J-55 d 51 sxs cmt. LDT/CNL/DLL/MSFL/GR logs. C" + 275 sx Class "C". Circ'd 95
Spudded this well on 7/26/97 at 0730 hr ST&C csg, set at 1190'. Cemented w/3 Drld 7 7/8" hole and reached TD 2650' Ran 60 jts 5 1/2" 15.5# J-55 LT&C csg sxs cmt.	rs and drld a 12 1/4" hole to 1191'. On 5/2 350 sxs lite "C" & 200 sxs lite "C". Circ' on 8/9/97 at 0200 hrs. Schlumberger rang, set at 2649'. Cemented w/250 sx lite "C".	any proposed work. If well is directionally drilled, give 27/97 ran 30 jts 8 5/8" 24# J-55 d 51 sxs cmt. LDT/CNL/DLL/MSFL/GR logs. C" + 275 sx Class "C". Circ'd 95
Spudded this well on 7/26/97 at 0730 hr ST&C csg, set at 1190'. Cemented w/3 Drld 7 7/8" hole and reached TD 2650' Ran 60 jts 5 1/2" 15.5# J-55 LT&C csg sxs cmt.	rs and drld a 12 1/4" hole to 1191'. On 5/2 350 sxs lite "C" & 200 sxs lite "C". Circ' on 8/9/97 at 0200 hrs. Schlumberger rang, set at 2649'. Cemented w/250 sx lite "C".	any proposed work. If well is directionally drilled, give 27/97 ran 30 jts 8 5/8" 24# J-55 d 51 sxs cmt. LDT/CNL/DLL/MSFL/GR logs. C" + 275 sx Class "C". Circ'd 95
Spudded this well on 7/26/97 at 0730 hr ST&C csg, set at 1190'. Cemented w/3 Drld 7 7/8" hole and reached TD 2650' Ran 60 jts 5 1/2" 15.5# J-55 LT&C csg sxs cmt.	rs and drld a 12 1/4" hole to 1191'. On 5/2 350 sxs lite "C" & 200 sxs lite "C". Circ' on 8/9/97 at 0200 hrs. Schlumberger rang, set at 2649'. Cemented w/250 sx lite "C".	any proposed work. If well is directionally drilled, give 27/97 ran 30 jts 8 5/8" 24# J-55 d 51 sxs cmt. LDT/CNL/DLL/MSFL/GR logs. C" + 275 sx Class "C". Circ'd 95 ROSWEE - ROSWEE
Spudded this well on 7/26/97 at 0730 hr ST&C csg, set at 1190'. Cemented w/3 Drld 7 7/8" hole and reached TD 2650' Ran 60 jts 5 1/2" 15.5# J-55 LT&C csg sxs cmt. Released rig at 1430 hrs 8/10/97. WOC	rs and drld a 12 1/4" hole to 1191'. On 5/2 350 sxs lite "C" & 200 sxs lite "C". Circ' on 8/9/97 at 0200 hrs. Schlumberger rang, set at 2649'. Cemented w/250 sx lite "C".	any proposed work. If well is directionally drilled, give 27/97 ran 30 jts 8 5/8" 24# J-55 d 51 sxs cmt. LDT/CNL/DLL/MSFL/GR logs. C" + 275 sx Class "C". Circ'd 95 ROSWOF LOFT OF CONTROL OF CONTR
Spudded this well on 7/26/97 at 0730 hr ST&C csg, set at 1190'. Cemented w/3 Drld 7 7/8" hole and reached TD 2650' Ran 60 jts 5 1/2" 15.5# J-55 LT&C csg sxs cmt. Released rig at 1430 hrs 8/10/97. WOC	rs and drld a 12 1/4" hole to 1191'. On 5/2 350 sxs lite "C" & 200 sxs lite "C". Circ' on 8/9/97 at 0200 hrs. Schlumberger rang, set at 2649'. Cemented w/250 sx lite "C".	any proposed work. If well is directionally drilled, give 27/97 ran 30 jts 8 5/8" 24# J-55 d 51 sxs cmt. LDT/CNL/DLL/MSFL/GR logs. C" + 275 sx Class "C". Circ'd 95 ROSWEE - ROSWEE
Spudded this well on 7/26/97 at 0730 hr ST&C csg, set at 1190'. Cemented w/3 Drld 7 7/8" hole and reached TD 2650' Ran 60 jts 5 1/2" 15.5# J-55 LT&C csg sxs cmt.	rs and drld a 12 1/4" hole to 1191'. On 5/2 50 sxs lite "C" & 200 sxs lite "C". Circ' on 8/9/97 at 0200 hrs. Schlumberger rang, set at 2649'. Cemented w/250 sx lite "C".	any proposed work. If well is directionally drilled, give 27/97 ran 30 jts 8 5/8" 24# J-55 d 51 sxs cmt. LDT/CNL/DLL/MSFL/GR logs. C" + 275 sx Class "C". Circ'd 95 ROSWELL OFFLAND ROSWELL
Spudded this well on 7/26/97 at 0730 hr ST&C csg, set at 1190'. Cemented w/3 Drld 7 7/8" hole and reached TD 2650' Ran 60 jts 5 1/2" 15.5# J-55 LT&C csg sxs cmt. Released rig at 1430 hrs 8/10/97. WOC	es and drld a 12 1/4" hole to 1191'. On 5/2 350 sxs lite "C" & 200 sxs lite "C". Circ' on 8/9/97 at 0200 hrs. Schlumberger rang, set at 2649'. Cemented w/250 sx lite "C". ACCOUNTY OF THE PROPERTY OF THE PR	any proposed work. If well is directionally drilled, give 27/97 ran 30 jts 8 5/8" 24# J-55 d 51 sxs cmt. LDT/CNL/DLL/MSFL/GR logs. C" + 275 sx Class "C". Circ'd 95 ROSWOF LOFT OF CONTROL OF CONTR
Spudded this well on 7/26/97 at 0730 hr ST&C csg, set at 1190'. Cemented w/3 Drld 7 7/8" hole and reached TD 2650' Ran 60 jts 5 1/2" 15.5# J-55 LT&C csg sxs cmt. Released rig at 1430 hrs 8/10/97. WOC	rs and drld a 12 1/4" hole to 1191'. On 5/2 50 sxs lite "C" & 200 sxs lite "C". Circ' on 8/9/97 at 0200 hrs. Schlumberger rang, set at 2649'. Cemented w/250 sx lite "C".	any proposed work. If well is directionally drilled, give 27/97 ran 30 jts 8 5/8" 24# J-55 d 51 sxs cmt. LDT/CNL/DLL/MSFL/GR logs. C" + 275 sx Class "C". Circ'd 95 ROSWELL OFFLAND ROSWELL
Spudded this well on 7/26/97 at 0730 hr ST&C csg, set at 1190'. Cemented w/3 Drld 7 7/8" hole and reached TD 2650' Ran 60 jts 5 1/2" 15.5# J-55 LT&C csg sxs cmt. Released rig at 1430 hrs 8/10/97. WOC	es and drld a 12 1/4" hole to 1191'. On 5/2 350 sxs lite "C" & 200 sxs lite "C". Circ' on 8/9/97 at 0200 hrs. Schlumberger rang, set at 2649'. Cemented w/250 sx lite "C". ACCOUNTY OF THE PROPERTY OF THE PR	any proposed work. If well is directionally drilled, give 27/97 ran 30 jts 8 5/8" 24# J-55 d 51 sxs cmt. LDT/CNL/DLL/MSFL/GR logs. C" + 275 sx Class "C". Circ'd 95 ROSWELL OFFLAND ROSWELL
Spudded this well on 7/26/97 at 0730 hr ST&C csg, set at 1190'. Cemented w/3 Drld 7 7/8" hole and reached TD 2650' Ran 60 jts 5 1/2" 15.5# J-55 LT&C csg sxs cmt. Released rig at 1430 hrs 8/10/97. WOC	es and drld a 12 1/4" hole to 1191'. On 5/2 350 sxs lite "C" & 200 sxs lite "C". Circ' on 8/9/97 at 0200 hrs. Schlumberger rang, set at 2649'. Cemented w/250 sx lite "C". ACCOUNTY OF THE PROPERTY OF THE PR	any proposed work. If well is directionally drilled, give 27/97 ran 30 jts 8 5/8" 24# J-55 d 51 sxs cmt. LDT/CNL/DLL/MSFL/GR logs. C" + 275 sx Class "C". Circ'd 95 ROSWELL OFFLAND ROSWELL
Spudded this well on 7/26/97 at 0730 hr ST&C csg, set at 1190'. Cemented w/3 Drld 7 7/8" hole and reached TD 2650' Ran 60 jts 5 1/2" 15.5# J-55 LT&C csg sxs cmt. Released rig at 1430 hrs 8/10/97. WOC	es and drld a 12 1/4" hole to 1191'. On 5/2 550 sxs lite "C" & 200 sxs lite "C". Circ's on 8/9/97 at 0200 hrs. Schlumberger rang, set at 2649'. Cemented w/250 sx lite "C". U. Crystal Thorrion Title Engineering Technician	any proposed work. If well is directionally drilled, give 27/97 ran 30 jts 8 5/8" 24# J-55 d 51 sxs cmt. LDT/CNL/DLL/MSFL/GR logs. C" + 275 sx Class "C". Circ'd 95 ROSWELL OFF LAND CHARLE