

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE

FORM APPROVED

C/SF

(See other instructions on reverse side)

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL: OIL WELL ☒ GAS WELL ☐ DRY ☐ Other ☐ NS

b. TYPE OF COMPLETION:

SLW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR ☐ Other ☐ N 2834

2. NAME OF OPERATOR

DEVON ENERGY CORPORATION (NEVADA)

3. ADDRESS AND TELEPHONE NO.

20 N. BROADWAY, SUITE 1500, OKC, OK 73102-8260 (405) 235-3611

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface 990' FNL & 1880' FEL, Unit "B"

At top prod. interval reported below (SAME)

At total depth (SAME)

5. LEASE DESIGNATION AND SERIAL NO.

LC-065478-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

NA

7. UNIT AGREEMENT NAME

NA

8. FARM OR LEASE NAME, WELL NO.

Falcon "3B" Federal #2

9. API WELL NO.

30-015-29542

10. FIELD AND POOL, OR WILDCAT

Red Lake (Q-GB-SA)

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA "B", Section 3-18S-27E

14. PERMIT NO.

BLM

DATE ISSUED

4/24/97

12. COUNTY OR PARISH

Eddy County

13. STATE

NM

15. DATE SPUDDED

5/31/97

16. DATE T.D. REACHED

6/14/97

17. DATE COMPLETED

6/27/97

18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*

KB 3595'; GL 3586'; DF 3594'

19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD

2699'

21. FLOG, BACK T.D., MD & TVD

2654'

22. IF MULTIPLE COMPLETIONS, HOW MANY*

NA

23. INTERVALS

DRILLED BY

ROTARY TOOLS

X

CABLE TOOLS

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND T/D)*

San Andres - 1650-2372'

JUL 8 1 1997

25. WAS DIRECTIONAL SURVEY

MADE

No

26. TYPE ELECTRIC AND OTHER LOGS RUN

LDT/CNL/DLL/MSFL/GR; CBL

27. WAS WELL CORED

No

28.

CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
8-5/8" J-55	24#	1150'	12-1/4"	surf; 300 sxs lite & 200 sxs "C"	NA
5-1/2" J-55	15.5#	2800'	7-7/8"	surf; 150 sxs lite C & 350 sxs "C"	NA

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	BACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2-7/8"	2140'	(OET)

30. TUBING RECORD

31. PERFORATION RECORD (Interval, size and number)

1650-1780' U. SA, (4 -40" EHD holes)

1919-2054' ALPHA (7 -40" EHD holes)

2136-2165' "A" (3 -40" EHD holes)

2188-2288' "B" (8 -40" EHD holes)

2302-2316' "C" (5 -40" EHD holes)

2359-2372' "D" (3 -40" EHD holes)

32. ACID SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
1650-2372'	2500 gals of 15% NeFe acid
1650-2372'	180,200 gals gel water + 6000# 100 mesh sand
	+ 86,000# 20/40 & 157,000# 16/30 Brady
	sand ISIP 1200#, closed at 1030#.

33.*

PRODUCTION

DATE FIRST PRODUCTION 7/2/97		PRODUCTIONS METHOD I(Flowing, gas lift, pumping—size and type of pump) Pumping (2-1/2" x 2" x 12' RWTC Pump)					WELL STATUS (Producing or shut-in) Producing	
DATE OF TEST 7/12/97	HOURS TESTED 24	CHOKO SIZE	PROD'N FOR TEST PERIOD →	OIL-BBL. 118	GAS-MCF. 118	WATER-BBL. 191	GAS-OIL RATIO 1000/1	
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE →	OIL-BBL. 118	GAS-MCF. 118	WATER-BBL. 191	OIL GRAVITY-API (CORR.) 38°		

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

Vented (To be connected)

TEST WITNESSED BY

Danny Hokett

35. LIST OF ATTACHMENTS

Logs, Deviation Surveys

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

Crystal Thornton

TITLE ENGINEERING TECHNICIAN

DATE July 16, 1997

(See Instructions and Spaces for Additional Data on Reverse Side)

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):				38. GEOLOGIC MARKERS		
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
Premier Sand San Andres	1548'	1595'	sandstone dolomite	Bowers	666'	+2929
	1595'	2699'		Queen	862'	+2733
				Grayburg	1548'	+3595
				Premier	1595'	+2047
				San Andres		+2000
		DEPTH	ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.. (continued from the front)			
		NA				