

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE

FORM APPROVED

(See other
instructions on
reverse side)

CISF

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL: OIL WELL ☒ GAS WELL ☐ DRY ☐ Other ☐

b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESRV. ☐ Other ☐

2. NAME OF OPERATOR

DEVON ENERGY CORPORATION (NEVADA)

3. ADDRESS AND TELEPHONE NO.

20 N. BROADWAY, SUITE 1500, OKC, OK 73102-3201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)

At surface 840' FNL & 990' FWL, Unit "D"

At top prod. interval reported below (SAME)

At total depth (SAME)

5. LEASE DESIGNATION AND SERIAL NO.
LC-065478-B6. IF INDIAN, ALLOTTEE OR TRIBE NAME
NA7. UNIT AGREEMENT NAME
(NA)8. FARM OR LEASE NAME, WELL NO.
Falcon "3D" Federal #69. API WELL NO.
30-015-2954410. FIELD AND POOL, OR WILDCAT
Red Lake (Q-GB-SA)11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA
"D", Section 3-18S-27E

12. COUNTY OR PARISH
Eddy County

13. STATE
NM

14. PERMIT NO.
BLM

15. DATE SPOOLED
6/6/97

16. DATE T.D. REACHED
6/11/97

17. DATE COMPL. (Ready to prod.)
6/28/97

18. ELEVATIONS (DP, RKB, RT, GR, ETC.)
KB 3580'; GL 3517'; DF 3579'

19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD
2649'

21. FLOG, BACK T.D., MD & TVD
2604'

22. IF MULTIPLE COMPL., HOW MANY?
NA

23. INTERVALS
DRILLED BY

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME
San Andres - 1829-2302'

25. WAS DIRECTIONAL SURVEY
MADE
No

26. TYPE ELECTRIC AND OTHER LOGS RUN
LDT/CNL/DLL/MSFL/GR; CBL27. WAS WELL CORED
No

28. CASING RECORD (Report all strings set in well)					
CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
8-5/8" J-55	24#	1151'	12-1/4"	surf; 350 sxs lite & 200 sxs "C"	NA
5-1/2" J-55	15.5#	2650'	7-7/8"	surf; 225 sxs lite C & 250 sxs "C"	NA

29. LINER RECORD					30. TUBING RECORD		
SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2-7/8"	2010'	(OET)

31. PERFORATION RECORD (Interval, size and number)

1829-1938' ALPHA (7-40" EHD holes)

2022-2090' "A" (7-40" EHD holes)

2109-2174' "B" (7-40" EHD holes)

2213-2243' "C" (5-40" EHD holes)

2271-2302' "D" (4-40" EHD holes)

32. ACID SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
1829-2302'	2500 gals of 15% NeFe acid
1829-2302"	180,000 gals gel water + 6000# 100 mesh sand
	86,000# 20/40 and 157,000# 16/30
	Brady Sand. ISIP 875#, closed at 586#.

33.* PRODUCTION							
DATE FIRST PRODUCTION 7/13/97		PRODUCTIONS METHOD 1 (Flowing, gas lift, pumping—size and type of pump) Pumping (2-1/2" x 2" x 12' RWTC Pump)					WELL STATUS (Producing or shut-in) Producing
DATE OF TEST 7/13/97	HOURS TESTED 24	CHOKER SIZE	PROD'N FOR TEST PERIOD	OIL-BEL. 155	GAS-MCF. 155	WATER-BEL. 371	GAS-OIL RATIO 1000/1
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL-BEL. 155	GAS-MCF. 155	WATER-BEL. 371	OIL GRAVITY-API (CORR.) 38°	

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)
Vented (To be connected)TEST WITNESSED BY
Danny Hokett35. LIST OF ATTACHMENTS
Logs, Deviation Surveys

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED Crystal ThorntonCRYSTAL THORNTON
TITLE ENGINEERING TECHNICIAN

DATE July 17, 1997

*(See Instructions and Spaces for Additional Data on Reverse Side)

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):				38. GEOLOGIC MARKERS		
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	MEAS. DEPTH	TOP TRUE VERT. DEPTH
Premier Sand San Andres	1503' 1552'	1552' 2650'	sandstone dolomite	Bowers Queen Grayburg Premier San Andres	641' 833' 1503' 1552'	+2939 +2747 +3580 +2077 +2028
		DEPTH	ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.. (continued from the front)			
		NA				