

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1650' FSL & 1650' FWL of Section 15-T18S-R29E (Unit K, NESW)

5. Lease Designation and Serial No.

NM-96220

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Arenas ARI Fed Com #1

9. API Well No.

30-015-29629

10. Field and Pool, or Exploratory Area

Turkey Track Morrow North

11. County or Parish, State

Eddy Co., NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Spud, resume drilling, surface casing & cement

☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spudded a 20" hole with rat hole machine at 9:45 AM 6-6-97. Set 40' of 16" conductor pipe. Cemented to surface. NOTE: Notified Cathy Queen w/BLM-Carlsbad of spud. Resumed drilling a 14-3/4" hole with rotary tools at 8:30 PM 6-7-97.

TD 375'. Reached TD at 4:15 AM 6-8-97. Ran 9 joints of 11-3/4" 42# H-40 (378.83') of casing set at 375'. 1-Texas Pattern notched guide shoe set at 375'. Insert float set at 335'. Cemented with 200 sacks Class H, 10% A-10B, 10#/sack gilsonite, 1/4#/sack celloflake and 1% CaCl2 (yield 1.52, weight 14.6) and 200 sacks BJ Lite C, 5#/sack gilsonite, 6% gel, and 2% CaCl2 (yield 1.93, weight 12.6). Tailed in with 200 sacks Class C 2% CaCl2 (yield 1.34, weight 14.8). PD 9:45 AM 6-8-97. Bumped plug to 700 psi, OK. Cement did not circulate. WOC 5-1/4 hours. Ran 1". Tagged cement at 156'. Spotted 50 sacks Class C 4% CaCl2. PD 3:30 PM 6-8-97. WOC 1 hour. Ran 1". Tagged cement at 156'. Spotted 75 sacks Class C 4% CaCl2. PD 5:00 PM 6-8-97. WOC 1 hour. Ran 1". Tagged cement at 156'. Spotted 50 sacks Class C 4% CaCl2. PD 6:30 PM 6-8-97. WOC 1 hour. Ran 1". Tagged cement at 156'. Spotted 35 sacks Class C 4% CaCl2. PD 8:00 PM 6-8-97. WOC 2 hours. Ran 1". Tagged cement at 156'. Spotted 25 sacks Class C 4% CaCl2. PD 10:30 PM 6-8-97. WOC 2-1/2 hours. Ran 1". Tagged cement at 85'. Spotted 50 sacks Class C 4% CaCl2. PD 1:30 AM 6-9-97. Circulated 10 sacks. WOC. Cut off and weld on flow nipple. Drilled out at 2:00 PM 6-9-97. WOC 28 hours and 15 minutes. Reduced hole to 11". Resumed drilling.

14. I hereby certify that the foregoing is true and correct

Signed *David R. Glan*

Title Operations Technician

Date June 12, 1997

(This space for Federal or State office use)

Approved by  
Conditions of approval, if any:

Title

ACCEPTED FOR RECORD

(ORIG. SGD) DAVID R. GLAN

JUN 18 1997

Date