

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1650' FSL & 1650' FWL of Section 15-T18S-R29E (Unit K, NESW)

5. Lease Designation and Serial No.

NM-96220

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Azenas ARI Fed Com #1

9. API Well No.

30-015-29629

10. Field and Pool, or Exploratory Area

Turkey Track Morrow, North

11. County or Parish, State

Eddy Co., NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Intermediate casing & cement
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 3210'. Reached TD at 4:30 PM 6-13-97. Ran 73 joints of 8-5/8" 32# J-55 8rd ST&C (3218.14') of casing set at 3204'. Float shoe set at 3204'. Float collar set at 3157'. Cemented with 900 sacks C (65-35-6), 1/4#/sack celloflake and 10#/sack salt (yield 2.02, weight 12.8). Tailed in with 200 sacks C with 2% CaCl₂ (yield 1.34, weight 14.8). PD 8:15 AM 6-14-97. Bumped plug to 1600 psi, OK. Circulated 64 sacks. WOC. Nipped up and tested to 500 psi for 30 minutes. Drilled out at 8:00 AM 6-15-97. WOC 23 hours and 45 minutes. Reduced hole to 7-7/8". Resumed drilling.

14. I hereby certify that the foregoing is true and correct

Signed

Title Operations Technician

Date June 16, 1997

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

ACCEPTED FOR RECORD
(ORIG. SGD.) DAVID R. GLASS
JUN 18 1997

Date