Submit 3 Copies to Appropriate District Office	nergy, Minera		f New Mexico Natural Resources Depar. Int	CISI	Form C-103 Revised 1-1-89	
DISTRICT I P.O. Box 1980, Hobbs, NM 88240	OIL CONSERVATION DIVISION			WELL AND O 30-015-29861		
DISTRICT II P.O. Drawer DD, Artesia, NM 88210	P.O. Box 2088 Santa Fe, New Mexico 87504-2088			5. Indicate Typ	e of Lease STATE FEE	
DISTRICT III 1000 rio Brazos Rd, Aztec, NM 87410	· · · · · · · · · · · · · · · · · · ·		2335	6. State Oil & 0		
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)				7. Lease Name or Unit Agreement Name Jackson		
1. Type of Well Oil Well Gas Well	Other					
2. Name of Operator DEVON ENERGY (CORPORATION (NEVADA)		(₹ DEC 1997 RECEIVED	8. Well No.		
3. Address of Operator	WAY SUITE 1500 OKI AHOMA CITY	/ OKLA	ncn - ARTESIA	9. Pool name o		
20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405) 235-3611					-db-3A)	
Unit Letter M:330 Fee	t From The <u>south</u>		Line and 660 91 91 VI Feet 1	From The <u>west</u>	Line	
Section 7	Township 18S	Range		Eddy	County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3284' GL						
Check Appropriate Box To Indicate Nature Of Notice, Report, Or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING						
TEMPORARILY ABANDON PULL OR ALTER CASING OTHER:	☐ CHANGE PLANS		COMMENCE DRILLING OPNS. CASING TEST AND CEMENT JOB OTHER: completion	PLUG AI	ND ABANDONMENT	
13. Describe Proposed or Completed	Operations (Clearly state all pertinent details, an	d give peri	inent dates, including estimated date of starting ar	ny proposed work.) S	SEE RULE 1103	
11/18/97 RU Wedge WL, Ran CR/CCL/CBL/VDL logs from PBTD (2107') to surf. Perf'd San Andres formation w/1 SPF as follows: 1349', 1410', 24', 26', 1525', 36', 45', 64', 68', 74', 86', 93', 1614', 49', 56', 67', 89', 96', 1703', 12', 14', 16', 18', 20', 24', 28', 38', 52', 64', 86', and 1808', for a total of 31 holes (.40" EHD Holes).						
Acidize San Andres perfs 1349-1808' w/2500 gals of 15% NeFe acid, ISIP 920#.						
Fracture treated San Andres perfs 1349-1808' w/180,000 gals linear gelled water with 6000# mesh sand, and 306,000# of 20/40 Brady Sand. ISIP 1168#, closed @ 960#.						
Ran 2 7/8" production tbg, SN set at 1550'. Ran pump and rods. Began pump testing.						
I hereby certify that the information above is true and complete to the best of my knowledge and belief.						
SIGNATURE / COLUMN	a souz	TITLE	ENGINEERING TECHNICIAN	•	ember 22, 1997	
	Diana Keys			TELEPHON	E NO. (405) 235-3611	
(This space for State use) ORIGIFER Approved by DISTRICT Conditions of approval, if any:	L SIGNED BY TIM W. GUM	TITLE		DATE	2-17-98	