

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE *
(Other Instructions on
reverse side)

Budget Bureau No. 1004-0135
Expires August 31, 1985

c/57

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT - " for such proposals.)

1. <input checked="" type="checkbox"/> OIL <input type="checkbox"/> GAS <input type="checkbox"/> OTHER		5. LEASE DESIGNATION AND SERIAL NO. LC-029418-B	
2. NAME OF OPERATOR The Wiser Oil Company		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR P.O. Box 2568 Hobbs, New Mexico 88241		7. UNIT AGREEMENT NAME Lea "D"	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1330' FNL & 1330' FWL Sec. 26-T17S-R31E Unit F		8. API WELL NO. 30-015-29703	
		9. WELL NO. 23	
		10. FIELD AND POOL, OR WILDCAT Grayburg Jackson 7-Rivers	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 26-T17S-R31E	
14. PERMIT NO	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3839'	12. COUNTY OR PARISH Eddy	13. STATE NM

16. Check Appropriate Box to indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT OFF <input type="checkbox"/>	PULL OR ALTER CASING <input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	MULTIPLE COMPLETE <input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	ABANDON* <input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF <input type="checkbox"/>	REPAIRING WELL <input type="checkbox"/>
FRACTURE TREATMENT <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
SHOOTING OR ACIDIZING <input type="checkbox"/>	ABANDONMENT * <input checked="" type="checkbox"/>

(Other) Perforate & Acidize

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS: (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

12/06/97 HES perforated San Andres Upper Jackson f/3861'-74', 78', 79', 80', 82'-3900', 3910', 15', 20' and 24'-31' w/1 SPF (47 holes). RIH w/5-1/2" Baker pkr. on 2-7/8" tbg. to 3670'.

12/08/97 HES acidized San Andres Upper Jackson perfs. 3861'-3931' w/5000 gals. 15% NE-FE acid + 70 ball sealers. Formation broke @ 2978#. ATP 2360# @ 4.2 bpm. MTP 2843# @ 5 bpm. Good ball action. ISIP 2300#. 5 min. 2119#. 10 min. 2019#. 15 min. 1962#.

12/16/97 POH w/tbg. HES perforated San Andres Vacuum f/3726', 27', 32', 33', 34', 48', 49', 50', 52', 78', 79', 92', 3812', 21', 22', and 26' w/4 SPF (64 holes). RIH w/5-1/2" Baker RBP and 5-1/2" Baker pkr. on 2-7/8" tbg. Set RBP @ 3850'. Spotted 2 sx. sand on RBP. Pulled to 3610'.

12/17/97 Spotted acid and set pkr. @ 3605'. HES acidized San Andres Vacuum perfs. 3726'-3826' w/2500 gals. 15% NE-FE acid + 96 ball sealers. Formation broke @ 2450#. ATP 2276# @ 3.4 bpm. MTP 3015# @ 4.5 bpm. Did not ball out. Had good ball action. ISIP 2359#. 5 min. 2098#. 10 min. 1779#. 15 min 1586#.

12/18/97 HES circulated hole w/brine to kill well. POH w/tbg. and pkr. RIH w/2-7/8" tbg. ND BOP. Set TAC w/10,000# tension. Installed WH. RIH w/rods & 2-1/2" x 1-3/4" x 16' RHTC pump. Left well pumping to battery. Tbg. @ 3626'. SN @ 3591'. TAC @ 3371'.

01/07/98 POH w/rods & pump. NU BOP. Unset TAC. Circulated hole w/60 bbls. brine. POH w/tbg. RIH w/retrieving head on 2-7/8" tbg. Attempted to retrieve RBP. 15' fill. No success. Pulled 2 stands tbg.

18. I hereby certify that the foregoing is true and correct.

SIGNED Mary Jo Turner TITLE Completion Department DATE March 14, 1997

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instruction On Reverse Side