Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

N.M. Oil C 3. Division 811 S. 1st Street

FORM APPROVED

	21 O11 OOL	Budget bureau No. 1004-013
rtesia,	NM 8821	5. Lease Designation and Serial No.

SUNDRY NOTICES AN		NM-97122
Oo not use this form for proposals to drill o	ND REPORTS ON WELLS or to deepen or reentry to a different reservoir. PERMIT-" for such proposals	6. If Indian, Allottee or Tribe Name
SUBMIT IN	TRIPLICATE	7. If Unit or CA, Agreement Designation
. Type of Well	/∂j" A '\\	
Oil Gas ───────────────────────────────────	/AV 800 cm	8. Well Name and No.
. Name of Operator	N PECC. W	Chalk Federal #2
SDX Resources, Inc.	O DELETIVED N	9. API Well No.
. Address and Telephone No.	ARTESIA 57	30-015-29706
PO Box 5061, Midland, TX 79704 915/685-17	761	10. Field and Pool, or Exploratory Area
Location of Well (Footage, Sec., T., R., M., or Survey Descrip	otion)	Red Lake, QN-GB-SA
1980' FNL 2310' FWL Sec 5, T18S, R27E, Unit F	761 Stion) ARTESIA STILLELZILIOIS	11. County or Parish, State
		Eddy Co., NM
2. CHECK APPROPRIATE BOX(s) T	O INDICATE NATURE OF NOTICE, REPORT, O	R OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent	Abandonment	Change of Plans
	Recompletion	New Construction
Subsequent Report	Plugging Back	Non-Routine Fracturing
	Casing Repair	Water Shut-Off
Final Abandonment Notice	Altering Casing	Conversion to Injection
	Other	Dispose Water
		(Note: Report results of multiple completion on Well
Describe Proposed or Completed Operations (Clearly state directionally drilled, give subsurface locations and measured	all pertinet details, and give pertinent dates, including estimated date d and true vertical depths for all markders and zones pertinent to this v	Completion or Recompletion Report and Log form.) of starting any proposed work. If well is work.)"
directionally drilled, give subsurface locations and measured	d and true vertical depths for all markders and zones pertinent to this v 4#) from 600 sx Cl C to 200 sx Cl C w/2% CaCl & 1/4#/s	of starting any proposed work. If well is work.)*
Amend cement on surface csg (2250', 8-5/8", 24	d and true vertical depths for all markders and zones pertinent to this v 4#) from 600 sx Cl C to 200 sx Cl C w/2% CaCl & 1/4#/s	of starting any proposed work. If well is work.)*