Form 2160-5 (November 1983)		SUBMIT IN TRIPLICATE *	e			
(Formerly 9-331)	NITED STATES	(Other Instructions on reverse side)	Expires August 31, 1985			
DEPARTMENT OF THE INTERIOR			5. LEASE DESIGNATION AND SERIAL NO.			
RUREALLOF LAND MANAGEMENT			NM 98122			
	6. IF INDIAN, ALLOTTEE OR TRIBE NAME					
SUNDRY NOTICES AND REPORTS ON WELLS CE: V = 6. IF INDIAN, ALLOTTEE OR TRIBE NAME (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.						
Use "APPLICATION FOR PERMIT - " for such proposals.) 1997 SED 1 L A OLLO						
l			7. UNIT AGREEMENT NAME			
OIL GAS OTHER WELL Injection Well			Skelly Unit			
2. NAME OF OPERATOR						
The Wiser Oil Company			30-015-29712			
3. ADDRESS OF OPERATOR			9. WELL NO.			
			302			
P. O. Box 2568 Hobbs, New Mexico 88241			10. FIELD AND POOL, OR WILDCAT			
See also space 17 below.)			Grayburg Jackson 7-Rivers			
At surface 600' FNL & 583' FWL GOD BRIESS			11. SEC., T., R., M., OR BLK. AND			
Sec. 28-T17S-R31E			SURVEY OR AREA			
			Sec. 28-T17S-R31E			
14. PERMIT NO	15. ELEVATIONS (Show whether DF,	RT, GR, etc.)	12. COUNTY OR PARISH	13. STATE		
·	3767' DF		Eddy	NM		
16. Check Appropriate Box to indicate Nature of Notice, Report, or Other Data						
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:				
TEST WATER SHUT OFF	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL			
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT				
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	ALTERING CASING			
	ALMUNON		ABANDONMENT *			
REPAIR WELL	CHANGE PLANS	(Other) Spudding Ceme	nting Surface & Production Ca	sing		
			f multiple completion on Well	<u>ں ۔</u>		
(Other) Completion or Recompletion Report and Log form.)						

-1/17

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS: (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

MIRU Norton Drilling Co., Rig #5. Spudded 12-1/4" surface hole @ 3:15 p.m. 09/04/97. Drilled hole to 462'. Ran 10 jts. 8-5/8", 20#, ISW-42 ST& C csg. Set at 460'. Halliburton cemented with 400 sx. Class "C" containing 1/4#/sk. Flocele + 2% CaCl. Plug down @ 2:15 a.m., 09/05/97. Circulated 150 sx. cmt. BLM was notified, witnessed by Jim Amos. NU BOP & tested csg. to 1,000# for 30 min., no pressure loss. WOC 12 hrs.

Drilled 7-7/8" production hole to a depth of 3800". Ran casing as follows: Ran 91 jts. 5-1/2" 17#, J-55, LT&C csg. Set at 3800". Halliburton cemented w/1000 gals. Superflush 101 + 1100 sks. Halliburton Lite + 8# salt/sk. + 1/4# Flocele/sk. followed by 250 sks. Premium Plus w/3#KCL/sk. + .5% Halad 344 + 1/4# Flocele/sk. Displaced w/1 bbl. FW + 12 bbls. MSA + 74 bbls. FW w/Lo-Surf 300. Plug down at 11:00 a.m. 09/11/97. Circulated 10 sks. cmt. Rcleased rig at 1:00 p.m. 09/11/97. BLM was notified, no representative present. Pressure tested csg. to 1500# for 30 min., no pressure loss.

18 Ihereby certify that the foregoing is true and correct.				
SIGNED Mary Go Turan	TITLE	Drilling Department DATE September 15, 1997		
(This space for Federal or State office use)				
APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	_ TITLE _	ORIG. SGD.) DAVID R. GLRATE		
*See Instruction On Reverse Side				
Title 18 U.S.C. Section 1001, makes it a crime for any person statements or representations as to any matter within its jurisd		and willfully to make to any department or agency of the United States any false, fictitious or fraudulent		