Submit 3 Copies to Appropriate District Office	State of New Mexico Energy, Minerals and Natural Resources Department OIL CONSERVATION DIVISION P.O. Box 2088 Santa Fe, New Mexico 87504-2088		CIST Form C-103 Revised 1-1-89	
DISTRICT I P.O. Box 1980, Hobbs, NM \$8240 DISTRICT II P.O. Drawer DD, Artasia, NM \$8210 DISTRICT III 1000 Rio Brazos Rd., Aziec, NM \$7410			WELL API NO. 30-015-29791 5. Indicate Type of Lease STATE FEE 6. State Oil & Gas Lease No.	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			7. Lesse Name or Unit Agreement Name Atoka San Andres Unit	
1. Type of Well: OL OL X WELL X 2. Name of Operator Pennzoil Exploration & 1	oner Production Company		8. Well No. 164	
3. Address of Operator P O Box 50090 Midland 4. Well Location Unit Letter 234	Texas 79710-0090	Line and 125	9. Pool same or Wildest Atoka San Andres /81.5 Feet From The East Line	
Section 11	185		Eddy County	
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:				
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK COMMENCE DRILLING CASING TEST AND CE		
OTHER:	□	OTHER: New We	11	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spud well 9/29/97. Approval to proceed and intent to spud by Betty at NMOCD. Spud hole 12.25. Notified Tim w/NMOCD of intent to set surface casing 10/1/97. 8.625, 24#, K-55 csg. set at 954'. Circ. cmt, cmt. csg w/400 sxs 35/65 POZ w/additives, and 250 sx "C" w/additives Full circ. thruout job. Circ. 312 sx cmt to pits. Updated Tim w/NMOCD on cementing schedule 10/02/97. All casing in wellbore was new casing. Ran CNL/GR/NGT from TD to 200', LDT/DDL/ MSFL from TD to 954'. Ran 5.5, 15.5#, K-55 and 10 centralizers, cemented w/340 sxs. "C" w/additives, circulated cment. Circ. 58 sx cment to pits. Set 5.5" @ 1850'. Ran GR/CCL from TD to 1100'. See C-103 dated 8/17/98 for completion information. Rig released 10/07/98. Received verbal approval from Tim Gumm at 8:00 p.m. on 10/02/97 to change setting depth on surface casing.

I bereby cartify that the information above is true and complete to the best of my known SIONATURE	edge and belief. TTTLE Production Assistant	рате <u>8/20/98</u> 915 686-3505 тецерноме но.
(This space for State Use) Child Space for State Use) Child State Child Stat	TRLL	DATE