Form 3160-5 (November 1983) (Formerly 9-331)

## **UNITED STATES**

SUBMIT IN TRIPLICATE \* (Other Instructions on

Budget Bureau No. 1004-0135
Expires August 31. 1005

DEPARTMENT OF THE INTERIOR  RUPEAU OF LAND MANAGEMENT			5. LEASE DESIGNATION AND SERIAL NO. LC-029418-B	
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  Use "APPLICATION FOR PERMIT - " for such proposals.)			6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
OIL GAS WELL	OTHER	South Francisco	7. UNIT AGREEMENT NAME  Lea "D"	
2. NAME OF OPERATOR		K.	8. API WELL NO.	
The Wiser Oil Company  3. ADDRESS OF OPERATOR			9. WELL NO.	
P. O. Box 2568 Hobbs, New Mexico 88241			21	
	on clearly and in accordance with any Sta & 2597' FEL 178-R31E	te requirements ARTESIA	10. FIELD AND POOL, OR WILDCAT Grayburg Jackson 7-Rivers 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 26-T17S-R31E	
A DEDUCTION OF THE PROPERTY OF	T			
14. PERMIT NO	15. ELEVATIONS (Show whether DF 3761'	f, RT, GR, etc.)	12. COUNTY OR PARISH  Eddy	13. STATE NM
16. Check A	Appropriate Box to indicate Nat	ure of Notice, Report, or Othe		1 1111
NOTICE OF INTENTION TO:			BSEQUENT REPORT OF:	
TEST WATER SHUT OFF FRACTURE TREAT SHOOT OR ACIDIZE	PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON*	WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING	REPAIRING WELL  ALTERING CASING  ABANDONMENT *	
REPAIR WELL  (Other)	CHANGE PLANS	(Other) Spudding, Cementing Surface & Production Casing (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)		
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS: (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)  MIRU Norton Drilling Co., Rig #5. Spudded 12-1/4" surface hole @ 12:30 p.m. 11/02/97. Drilled hole to 464'. Ran 10 jts. 8-5/8", 20#, ISW-42 ST& C csg. Set at 459'. Halliburton cemented with 300 sx. Class "C" containing 1/4#/sk. Flocele + 2% CaCl. Plug down @ 8:30 p.m, 11/02/97. Circulated 35 sks. cmt. BLM was notified, no representative present. NU BOP & tested csg. to 1,000# for 30 min., no pressure loss. WOC 12 hrs.  Drilled 7-7/8" production hole to a depth of 4100'. Ran casing as follows: Ran 98 jts. 5-1/2" 17#, J-55, LT&C csg. Set at 4100'. Halliburton cemented w/1000 gals. Superflush 101 + 875 sks. Halliburton Lite + 8# salt/sk. + 1/4# Flocele/sk. followed by 250 sks. Premium Plus w/3#KCL/sk. + .5% Halad 344 + 1/4# Flocele/sk. Displaced w/1 bbl. FW # 12 bbls. MSA + 81 bbls. FW w/Lo-Surf 300. Plug down at 5:15 a.m. 11/09/97. Circulated 10 sks. cmt. Rcleased rig at 7:15 a.m. 11/09/97. BLM was notified, no representative present. Pressure tested csg. to 1500# for 30 min., no pressure loss.				
18 Ihereby certify that the foregoing is true ar	d correct.		· · · · · · · · · · · · · · · · · · ·	
SIGNED Mary Jo Turny	TITLE Drilling	Department	DATE November 10,	<u>1997</u>
(This space for Federal or State office use)  APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	TITLE		ACCEPTED FOR REC	

\*See Instruction On Reverse Side