

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. C. Cons. Division

311 S. 1st St.

Albuquerque, NM

8210-2834

FORM APPROVED

Bureau No. 1004-0135

Expires: March 31, 1993

C/SF

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Morexco, Inc.

3. Address and Telephone No.

P.O. Box 481 Artesia, NM 88211-0481 505-746-6520

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

2210' FNL & 2310' FWL (SE/4NW/4) SEC 5-18S-31E

5. Lease Designation and Serial No.

NM-68038

6. If Indian, Allottee or Tribe Name

NA

7. If Unit or CA, Agreement Designation

None

8. Well Name and No.

Shinnery Federal #1

9. API Well No.

30-015-29976

10. Field and Pool, or Exploratory Area

Undesignated Delaware

11. County or Parish, State

Eddy New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Casing

☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Spud well 12/17/97 @ 1:45 am w/ 12 1/4 bit. T.D. surface hole @ 440' ran 437' of 8 5/8 24# casing. Cemented w/ 350 sxs of class "C" w/ 2% Cacl + 1/4 celloflake, Cir 188 sxs to surface. Plug down @ 3:15 pm. Tested to 1000# held fine. 18 hrs WOC.

2. 12/18-12/31/97 Drilled to a T.D. of 4516' & logged.

3. Ran 104 Jts of 5 1/2 15.5# casing (4516'). Cemented w/ 860 sxs of class "C" lite w/ 1/4# celloflake + 350 sxs "H" A-10 B + 5% salt + 1/4# celloflake. cir 45 sxs to pit. Plug down @ 2:15 pm.

ACCEPTED FOR RECORD

JAN 21 1998

BLM

14. I hereby certify that the foregoing is true and correct

Signed

Title President

Date 1-7-98

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any: