Form 3160-5 (June 1990)

UNITED STATES DEPARTM IT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

M.M	
311 5	اد.
Art	a Nivi

Division

CIST

FORM APPROVED 210-2834 Bureau No. 1004-0135 Expires March 31, 1993

	AND REPORTS ON WELLS	5. Lease Designation and Serial No.
Do not use this form for proposals to drill or	r to deepen or reentry to a different reservoir.	LC-064384
Use "APPLICATION FO	R PERMIT—" for such proposals	6. If Indian, Allottee or Tribe Name
CUDMIT	IN TRIPLICATE	NA I
SUBINIT	IN TRIPLICATE	7. If Unit or CA, Agreement Designation
1. Type of Well		
[ŽÎ Oil Gas Other Well Other		O W.II No J No.
2. Name of Operator		8. Well Name and No.
DEVON ENERGY CORPORATION (NEVADA)		Carter Collier 5 Federal #9
3. Address and Telephone No.		9. API Well No.
	(LAHOMA CITY, OKLAHOMA 73102 (405) 235-3611	30-015-29995
		10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		Red Lake; Q-GB-SA
330' FNL & 2360' FEL of Section 5-18S-27E	±, Unit "B"	11. County or Parish, State
	The state of the s	Eddy County, NM
	Strong Park	Eddy Codinty, 14Wi
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NÖTICE, RE	PORT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	N
T N.: ST.	Abandonment	Change of Plans
Notice of Intent	Recompletion	New Construction
Subsequent Report	Plugging Back	Non-Routine Fracturing
Dubboquent Report	Casing Repair	Water Shut-Off
Final Abandonment Notice	Altering Casing	Conversion to Injection
_	Other Spud.csg string,TD	Dispose Water
		(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
Describe Proposed or Completed Operations (Clearly state all subsurface locations and measured and true vertical depths	pertinent details, and give pertinent dates, including estimated date of star for all markers and zones pertinent to this work.)*	Completion or Recompletion Report and Log form.)
subsurface locations and measured and true vertical depths	for all markers and zones pertinent to this work.)*	Completion or Recompletion Report and Log form.) ting any proposed work. If well is directionally drilled, give
subsurface locations and measured and true vertical depths Spud well on 4/22/98 at 1430 hrs and	drld a 12 1/4" hole to 1150'. On 4/24/98 ra	Completion or Recompletion Report and Log form.) ting any proposed work. If well is directionally drilled, give an 27 jts 8 5/8" 24# J-55 8RD ST&C
subsurface locations and measured and true vertical depths Spud well on 4/22/98 at 1430 hrs and	for all markers and zones pertinent to this work.)*	Completion or Recompletion Report and Log form.) ting any proposed work. If well is directionally drilled, give an 27 jts 8 5/8" 24# J-55 8RD ST&C
subsurface locations and measured and true vertical depths Spud well on 4/22/98 at 1430 hrs and	drld a 12 1/4" hole to 1150'. On 4/24/98 ra	Completion or Recompletion Report and Log form.) ting any proposed work. If well is directionally drilled, give an 27 jts 8 5/8" 24# J-55 8RD ST&C
subsurface locations and measured and true vertical depths Spud well on 4/22/98 at 1430 hrs and csg, set @ 1148'; cemented w/ 350 sx l	drld a 12 1/4" hole to 1150'. On 4/24/98 ralite "C" + 200 sx Class "C". 45 sx cmt retu	Completion or Recompletion Report and Log form.) ting any proposed work. If well is directionally drilled, give an 27 jts 8 5/8" 24# J-55 8RD ST&C rned to surface.
subsurface locations and measured and true vertical depths Spud well on 4/22/98 at 1430 hrs and csg, set @ 1148'; cemented w/ 350 sx l Drld 7 7/8" hole and reached TD 2455	drld a 12 1/4" hole to 1150'. On 4/24/98 ralite "C" + 200 sx Class "C". 45 sx cmt retu	Completion or Recompletion Report and Log form.) ting any proposed work. If well is directionally drilled, give an 27 jts 8 5/8" 24# J-55 8RD ST&C rned to surface. L/DLL/MSFL/GR logs. Ran 57 jts 5
subsurface locations and measured and true vertical depths Spud well on 4/22/98 at 1430 hrs and csg, set @ 1148'; cemented w/ 350 sx l Drld 7 7/8" hole and reached TD 2455	drld a 12 1/4" hole to 1150'. On 4/24/98 ralite "C" + 200 sx Class "C". 45 sx cmt retu	Completion or Recompletion Report and Log form.) ting any proposed work. If well is directionally drilled, give an 27 jts 8 5/8" 24# J-55 8RD ST&C rned to surface. L/DLL/MSFL/GR logs. Ran 57 jts 5
subsurface locations and measured and true vertical depths Spud well on 4/22/98 at 1430 hrs and csg, set @ 1148'; cemented w/ 350 sx l Drld 7 7/8" hole and reached TD 2455	for all markers and zones pertunent to this work.)* drld a 12 1/4" hole to 1150'. On 4/24/98 ra lite "C" + 200 sx Class "C". 45 sx cmt retu 5' on 4/27/98. Schlumberger ran LDT/CNI 2454'. Cemented w/ 200 sx lite "C" + 30	completion or Recompletion Report and Log form.) ting any proposed work. If well is directionally drilled, give an 27 jts 8 5/8" 24# J-55 8RD ST&C rned to surface. L/DLL/MSFL/GR logs. Ran 57 jts 5 00 sx Class "C". Circ'd 40 sx cmt.
subsurface locations and measured and true vertical depths Spud well on 4/22/98 at 1430 hrs and csg, set @ 1148'; cemented w/ 350 sx l Drld 7 7/8" hole and reached TD 2455	for all markers and zones pertunent to this work.)* drld a 12 1/4" hole to 1150'. On 4/24/98 ra lite "C" + 200 sx Class "C". 45 sx cmt retu 5' on 4/27/98. Schlumberger ran LDT/CNI 2454'. Cemented w/ 200 sx lite "C" + 30	completion or Recompletion Report and Log form.) ting any proposed work. If well is directionally drilled, give an 27 jts 8 5/8" 24# J-55 8RD ST&C rned to surface. L/DLL/MSFL/GR logs. Ran 57 jts 5 00 sx Class "C". Circ'd 40 sx cmt.
subsurface locations and measured and true vertical depths Spud well on 4/22/98 at 1430 hrs and csg, set @ 1148'; cemented w/ 350 sx l Drld 7 7/8" hole and reached TD 2455 1/2" 15.5# J-55 8RD LT&C csg, set @	drld a 12 1/4" hole to 1150'. On 4/24/98 ralite "C" + 200 sx Class "C". 45 sx cmt retu 5' on 4/27/98. Schlumberger ran LDT/CNI 2454'. Cemented w/ 200 sx lite "C" + 30	Completion or Recompletion Report and Log form.) ting any proposed work. If well is directionally drilled, give an 27 jts 8 5/8" 24# J-55 8RD ST&C rned to surface. L/DLL/MSFL/GR logs. Ran 57 jts 5 00 sx Class "C". Circ'd 40 sx cmt. CEPTED FOR RECORD
subsurface locations and measured and true vertical depths Spud well on 4/22/98 at 1430 hrs and csg, set @ 1148'; cemented w/ 350 sx l Drld 7 7/8" hole and reached TD 2455	drld a 12 1/4" hole to 1150'. On 4/24/98 ralite "C" + 200 sx Class "C". 45 sx cmt retu 5' on 4/27/98. Schlumberger ran LDT/CNI 2454'. Cemented w/ 200 sx lite "C" + 30	Completion or Recompletion Report and Log form.) ting any proposed work. If well is directionally drilled, give an 27 jts 8 5/8" 24# J-55 8RD ST&C rned to surface. L/DLL/MSFL/GR logs. Ran 57 jts 5 00 sx Class "C". Circ'd 40 sx cmt. CEPTED FOR RECORD
subsurface locations and measured and true vertical depths Spud well on 4/22/98 at 1430 hrs and csg, set @ 1148'; cemented w/ 350 sx l Drld 7 7/8" hole and reached TD 2455 1/2" 15.5# J-55 8RD LT&C csg, set @	drld a 12 1/4" hole to 1150'. On 4/24/98 ralite "C" + 200 sx Class "C". 45 sx cmt retu 5' on 4/27/98. Schlumberger ran LDT/CNI 2454'. Cemented w/ 200 sx lite "C" + 30	completion or Recompletion Report and Log form.) ting any proposed work. If well is directionally drilled, give an 27 jts 8 5/8" 24# J-55 8RD ST&C rned to surface. L/DLL/MSFL/GR logs. Ran 57 jts 5 00 sx Class "C". Circ'd 40 sx cmt.
subsurface locations and measured and true vertical depths Spud well on 4/22/98 at 1430 hrs and csg, set @ 1148'; cemented w/ 350 sx l Drld 7 7/8" hole and reached TD 2455 1/2" 15.5# J-55 8RD LT&C csg, set @	drld a 12 1/4" hole to 1150'. On 4/24/98 ralite "C" + 200 sx Class "C". 45 sx cmt retu 5' on 4/27/98. Schlumberger ran LDT/CNI 2454'. Cemented w/ 200 sx lite "C" + 30	completion or Recompletion Report and Log form.) ting any proposed work. If well is directionally drilled, give an 27 jts 8 5/8" 24# J-55 8RD ST&C rned to surface. L/DLL/MSFL/GR logs. Ran 57 jts 5 00 sx Class "C". Circ'd 40 sx cmt. CEPTED FOR RECORD MAY 1 5 1998
subsurface locations and measured and true vertical depths Spud well on 4/22/98 at 1430 hrs and csg, set @ 1148'; cemented w/ 350 sx l Drld 7 7/8" hole and reached TD 2455 1/2" 15.5# J-55 8RD LT&C csg, set @	drld a 12 1/4" hole to 1150'. On 4/24/98 ralite "C" + 200 sx Class "C". 45 sx cmt retu 5' on 4/27/98. Schlumberger ran LDT/CNI 2454'. Cemented w/ 200 sx lite "C" + 30	Completion or Recompletion Report and Log form.) ting any proposed work. If well is directionally drilled, give an 27 jts 8 5/8" 24# J-55 8RD ST&C rned to surface. L/DLL/MSFL/GR logs. Ran 57 jts 5 00 sx Class "C". Circ'd 40 sx cmt. CEPTED FOR RECORD
subsurface locations and measured and true vertical depths Spud well on 4/22/98 at 1430 hrs and csg, set @ 1148'; cemented w/ 350 sx l Drld 7 7/8" hole and reached TD 2455 1/2" 15.5# J-55 8RD LT&C csg, set @	drld a 12 1/4" hole to 1150'. On 4/24/98 ralite "C" + 200 sx Class "C". 45 sx cmt retu 5' on 4/27/98. Schlumberger ran LDT/CNI 2454'. Cemented w/ 200 sx lite "C" + 30	completion or Recompletion Report and Log form.) ting any proposed work. If well is directionally drilled, give an 27 jts 8 5/8" 24# J-55 8RD ST&C rned to surface. L/DLL/MSFL/GR logs. Ran 57 jts 5 00 sx Class "C". Circ'd 40 sx cmt. CEPTED FOR RECORD MAY 1 5 1998
subsurface locations and measured and true vertical depths Spud well on 4/22/98 at 1430 hrs and csg, set @ 1148'; cemented w/ 350 sx l Drld 7 7/8" hole and reached TD 2455 1/2" 15.5# J-55 8RD LT&C csg, set @	drld a 12 1/4" hole to 1150'. On 4/24/98 ralite "C" + 200 sx Class "C". 45 sx cmt retu 5' on 4/27/98. Schlumberger ran LDT/CNI 2454'. Cemented w/ 200 sx lite "C" + 30	completion or Recompletion Report and Log form.) ting any proposed work. If well is directionally drilled, give an 27 jts 8 5/8" 24# J-55 8RD ST&C rned to surface. L/DLL/MSFL/GR logs. Ran 57 jts 5 00 sx Class "C". Circ'd 40 sx cmt. CEPTED FOR RECORD MAY 1 5 1998
Spud well on 4/22/98 at 1430 hrs and csg, set @ 1148'; cemented w/ 350 sx l Drld 7 7/8" hole and reached TD 2455 1/2" 15.5# J-55 8RD LT&C csg, set @ Released rig @ 1000 hrs 4/28/98. WO	drld a 12 1/4" hole to 1150'. On 4/24/98 ralite "C" + 200 sx Class "C". 45 sx cmt retu 5' on 4/27/98. Schlumberger ran LDT/CNI 2454'. Cemented w/ 200 sx lite "C" + 30	completion or Recompletion Report and Log form.) ting any proposed work. If well is directionally drilled, give an 27 jts 8 5/8" 24# J-55 8RD ST&C rned to surface. L/DLL/MSFL/GR logs. Ran 57 jts 5 00 sx Class "C". Circ'd 40 sx cmt. CEPTED FOR RECORD MAY 1 5 1998
subsurface locations and measured and true vertical depths Spud well on 4/22/98 at 1430 hrs and csg, set @ 1148'; cemented w/ 350 sx l Drld 7 7/8" hole and reached TD 2455 1/2" 15.5# J-55 8RD LT&C csg, set @	drld a 12 1/4" hole to 1150'. On 4/24/98 ralite "C" + 200 sx Class "C". 45 sx cmt retu 5' on 4/27/98. Schlumberger ran LDT/CNI 2454'. Cemented w/ 200 sx lite "C" + 30	completion or Recompletion Report and Log form.) ting any proposed work. If well is directionally drilled, give an 27 jts 8 5/8" 24# J-55 8RD ST&C rned to surface. L/DLL/MSFL/GR logs. Ran 57 jts 5 00 sx Class "C". Circ'd 40 sx cmt. CEPTED FOR RECORD MAY 1 5 1998
Spud well on 4/22/98 at 1430 hrs and csg, set @ 1148'; cemented w/ 350 sx l Drld 7 7/8" hole and reached TD 2455 1/2" 15.5# J-55 8RD LT&C csg, set @ Released rig @ 1000 hrs 4/28/98. WO	drld a 12 1/4" hole to 1150'. On 4/24/98 ralite "C" + 200 sx Class "C". 45 sx cmt returned by the state of th	completion or Recompletion Report and Log form.) ting any proposed work. If well is directionally drilled, give an 27 jts 8 5/8" 24# J-55 8RD ST&C rned to surface. L/DLL/MSFL/GR logs. Ran 57 jts 5 00 sx Class "C". Circ'd 40 sx cmt. CEPTED FOR RECORD MAY 1 5 1998
Spud well on 4/22/98 at 1430 hrs and csg, set @ 1148'; cemented w/ 350 sx l Drld 7 7/8" hole and reached TD 2455 1/2" 15.5# J-55 8RD LT&C csg, set @ Released rig @ 1000 hrs 4/28/98. WO	drld a 12 1/4" hole to 1150'. On 4/24/98 ralite "C" + 200 sx Class "C". 45 sx cmt returns on 4/27/98. Schlumberger ran LDT/CNI 2454'. Cemented w/ 200 sx lite "C" + 30 CU.	completion or Recompletion Report and Log form.) ting any proposed work. If well is directionally drilled, give an 27 jts 8 5/8" 24# J-55 8RD ST&C rned to surface. L/DLL/MSFL/GR logs. Ran 57 jts 5 00 sx Class "C". Circ'd 40 sx cmt. CEPTED FOR RECORD MAY 1 5 1998
Spud well on 4/22/98 at 1430 hrs and csg, set @ 1148'; cemented w/ 350 sx l Drld 7 7/8" hole and reached TD 2455 1/2" 15.5# J-55 8RD LT&C csg, set @ Released rig @ 1000 hrs 4/28/98. WO	drld a 12 1/4" hole to 1150'. On 4/24/98 ralite "C" + 200 sx Class "C". 45 sx cmt returned by the state of th	Completion or Recompletion Report and Log form.) ting any proposed work. If well is directionally drilled, give an 27 jts 8 5/8" 24# J-55 8RD ST&C rned to surface. L/DLL/MSFL/GR logs. Ran 57 jts 5 00 sx Class "C". Circ'd 40 sx cmt. CEPTED FOR RECORD MAY 1 5 1998 BLM Date 5/5/98
Spud well on 4/22/98 at 1430 hrs and csg, set @ 1148'; cemented w/ 350 sx l Drld 7 7/8" hole and reached TD 2455 1/2" 15.5# J-55 8RD LT&C csg, set @ Released rig @ 1000 hrs 4/28/98. WO 14. Thereby certify that the foregoing is true and correct Signed	drld a 12 1/4" hole to 1150'. On 4/24/98 ralite "C" + 200 sx Class "C". 45 sx cmt returned by the state of th	completion or Recompletion Report and Log form.) ting any proposed work. If well is directionally drilled, give an 27 jts 8 5/8" 24# J-55 8RD ST&C rned to surface. L/DLL/MSFL/GR logs. Ran 57 jts 5 00 sx Class "C". Circ'd 40 sx cmt. CEPTED FOR RECORD MAY 1 5 1998
Spud well on 4/22/98 at 1430 hrs and csg, set @ 1148'; cemented w/ 350 sx l Drld 7 7/8" hole and reached TD 2455 1/2" 15.5# J-55 8RD LT&C csg, set @ Released rig @ 1000 hrs 4/28/98. WO 14. Thereby certify that the foregoing is true and correct Signed	drld a 12 1/4" hole to 1150'. On 4/24/98 ralite "C" + 200 sx Class "C". 45 sx cmt returned by the state of the same of the state of the	Completion or Recompletion Report and Log form.) ting any proposed work. If well is directionally drilled, give an 27 jts 8 5/8" 24# J-55 8RD ST&C rned to surface. L/DLL/MSFL/GR logs. Ran 57 jts 5 00 sx Class "C". Circ'd 40 sx cmt. CEPTED FOR RECORD MAY 1 5 1998 BLM Date 5/5/98