Form 3160-3 (December 1990)					
			ATTEOR, NW	LC-026874-F	RIAL NO.
APPLICATION FOR PERMIT TO DRILL OR DEEPEN				6.IF INDIAN, ALLOTTRE OR T	RIBE NAME
la TYPE OF WORK: DRILL DEEPEN				NA	
	well Other	SINGLE	MULTIPLE	7.UNIT AGREEMENT NAME	
2 NAME OF OPERATOR DEVON ENERGY CORPORATION (NEVADA) (177				8. PARM OR LEASE HAME, WELL NO. Evarts 6 Federal #2 22363	
3. ADDRESS AND TELEPHONE NO. 20 N. BROADWAY, SUITE 1500, OKC, OK 73102 (405) 552-4511				9. APT WELL NO. 30-015- 30145	•
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)* At surface 1650' FNL & 999' FEL, Unit "H"				10. FIELD AND POOL, OR WILD Red Lake; Q-GB-SA	CAT
990				11.SEC.,T.,R.,M., OR BLOCK Section 6-T18S-27E	AND SURVEY OR AREA
	ND DIRECTION FROM MEAREST TOWN O southeast of Artesia, NM	POST OFFICE JAN 1998		2 12. COUNTY OR PARISE Fiddy County	13. STATE New Mexico
15.DISTANCE FROM PROPO LOCATION TO NEAREST	\$2D		RECEIVED	17.NO. OF ACR	
PROPERTY OR LEASE L: (Also to nearest drig, unit line		81	2 OCD - ARTESIA		
18.DISTANCE FROM PROPOSED LOCATION* TO MEAREST WELL, DRILLING, COMPLETED, OR APPLIED FOR, ON THIS LEASE, FT. 850'		19. PROPOSED DEPTH 2800'	1010 ve	Co 20. ROTARY OR C Rotary	CABLE TOOLS*
21. ELEVATIONS (Show whet GR 3467'	ther DF, RT, GR, etc.)		153420 2010	22. APPROX. DATE WORK February 1, 1998	WILL START*
		· · · · · · · · · · · · · · · · · · ·			
23. SIZE OF HOLE	GRADE, SIZE OF CASING	PROPOSED CASING AND C	EMINING SETTING DEPTH	TROLLED WATER	
17 1/2"	14''	Conductor	40'	Redimix	
12 1/4"	8 5/8", J-55	24 ppf	1150'		Class C
7 7/8"	5 1/2", J-55	15.5 ppf	2800'	150 sx Lite + 350	
* Cement will be circula	ated to surface on all casing strin	j.			
Devon Energy plans to will be plugged and aba	drill to 2800' +/- to test the San A andoned per Federal regulations.	ndres Formation for commercia Programs to adhere to onshore	al quantities of oil. If the San A e oil and gas regulations are ou	Andres is deemed non-commentation the following exhibit	rcial, the wellbore s and attachments.
Drilling Program Surface Use and Operat		The undersigned accepts all applicable terms, conditions, stipulation, and restrictions concerning operations conducted on the leased land or portion thereof, as described above.			
Exhibit #1 - Blowout Prevention Equipment/ Choke Manifold Exhibit #2 - Location and Elevation Plat		Bond Coverage: Nationwide BLM Bond File No.: CO-1104			
Exhibit #3 - Planned Access Roads Exhibit #4 - Wells Within a One Mile Radius			1.PPROV	AL SUBJECT TO-	
Exhibit #5 • Production Facilities Plan					IND J JED
Exhibit #6 - Rotary Rig	Layout ign Parameters and Factors		SPECIAL		
Exhibit #8 - H ₂ S Operating Plan					1-30.98
proposal is to drill or de	SCRIBE PROPOSED PROGRAM Repen directionally, give pertinen	M: If proposal is to deepen, give t data on subsurface locations a	e data on present productive zo and measured and true vertical	one and proposed new product	tive zone. If
24.	· · · · · · · · ·			······································	
	J.Bullins	E. L. B TITLE DISTR	UTTROSS, JR. RICT ENGINEER DA	TE <u> 2/16/9</u>	7
*(This space for Feder	ral or State office use)				
PERMIT NO			_ APPROVAL DATE _		
Application approval does n CONDITIONS OF APP	not warrant or certify that the applican PROVAL, IF ANY:	t holds legal or equitable title to thos	e rights in the subject lease which w	vould entitle the applicant to condu	ct operations thereon.
(OR)	G. SGD.) ARMAND o A. Lopez			DATE	5-9J
		See instructions On I	Reverse Side		

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

DISTRICT I P.O. Box 1980, Hobbs, NM 88240

DISTRICT II P.O. Drawer DD, Artesia, NM 88210

DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410 State of New Mexico

Energy, Minerals and Natural Resources Department

EXHIBIT #

Form C-102 Evised February 10, 1994 Instruction on back Submit to Appropriate District Office State Lease - 4 Copies Fee Lease - 3 Copies

OIL CONSERVATION DIVISION P.O. Box 2088 Santa Fe, New Mexico 87504-2088

WELL LOCATION AND ACREAGE DEDICATION PLAT

□ AMENDED REPORT

API Number Pool Code Pool Name Red Lake (O-GB-SA) **Property** Code **Property** Name Well Number Evarts 6 Federal 2 OGRID No. **Operator** Name Elevation Devon Energy Corporation 3467' Surface Location UL or lot No. Section Township Lot Idn Feet from the Range North/South line Feet from the East/West line County Η 6 18 S 27 E 1650 North 990 East Eddy Bottom Hole Location If Different From Surface UL or lot No. Section Township Range Lot Idn Feet from the North/South line Feet from the East/West line County ź Dedicated Acres Joint or Infill **Consolidation** Code Order No. NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION **OPERATOR CERTIFICATION** I hereby certify the the information contained herein is true and complete to the best of my knowledge and belief. Signatur 5 E. L. Buttross, jr. Printed Name District Engineer Title]2/]2/97 Date SURVEYOR CERTIFICATION I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervison, and that the same is true and correct to the best of my behaf. Novauloe 997 JONES Date Surveyor Signay Profes Sepimory re & Survey Certifi ider Sent 7977 BASIN SURVEY S



Attachment to Exhibit #1 NOTES REGARDING BLOWOUT PREVENTORS Evarts 6 Federal #2 Eddy County, New Mexico

- 1. Drilling nipple will be constructed so it can be removed mechanically without the aid of a welder. The minimum internal diameter will equal BOP bore.
- 2. Wear ring will be properly installed in head.
- 3. Blowout preventor and all associated fittings will be in operable condition to withstand a minimum 2000 psi working pressure.
- 4. All fittings will be flanged.
- 5. A full bore safety valve tested to a minimum 2000 psi WP with proper thread connections will be available on the rotary rig floor at all times.
- 6. All choke lines will be anchored to prevent movement.
- 7. All BOP equipment will be equal to or larger in bore than the internal diameter of the last casing string.
- 8. Will maintain a Kelly cock attached to the Kelly.
- 9. Hand wheels and wrenches will be properly installed and tested for safe operation.
- 10. All BOP equipment will meet API standards and include a minimum 40 gallon accumulator having two independent means of power to initiate closing operation.