Form C-103 State of New Mexico Submit 3 Copies Revised 1-1-89 Energy, Minerals and Natural Resources Department to Appropriate District Office DISTRICT I WELL API NO. OIL CONSERVATION DIVISION P.O. Box 1980, Hobbs, NM 88240 30-015-30050 P.O. Box 2088 5. Indicate Type of Lease DISTRICT II P.O. Drawer DD, Artesia, NM 88210 Santa Fe, New Mexico 87504-2088 FEE 🛛 STATE DISTRICT III 6. State Oil & Gas Lease No. 1000 rio Brazos Rd, Aztec, NM SUNDRY NOTICES AND REPORTS ON WELLS 7. Lease Name or Unit Agreement Name (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A Kaiser DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) Type of Well ☐ Gas Well Other 8. Well No. 2. Name of Operator **DEVON ENERGY CORPORATION (NEVADA)** 9. Pool name or Wildcat 3. Address of Operator 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405) 235-3611 Red Lake (Q-GB-SA) 4 Well Location Unit Letter A:890 Feet From The North Line and 625 Feet From The East **NMPM** County Township 18S Range 27E Section 18 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3290' GL Check Appropriate Box To Indicate Nature Of Notice, Report, Or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PLUG AND ABANDON REMEDIAL WORK ALTERING CASING PERFORM REMEDIAL WORK CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT TEMPORARILY ABANDON CASING TEST AND CEMENT JOB PULL OR ALTER CASING OTHER: Spud, Casing strings, TD OTHER: _ 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103. Spud well on 3/10/98 at 1300 hrs and drid a 17 1/2" hole to 127'. On 3/11/98 ran 3 jts 13 3/8" 48# H-40 8RD csg, set @ 140'. Cemented w/ 300 sx class "C". 75 sx cmt returned to surface. WOC Drid 12 1/4" hole to 1000'. On 3/13/98 ran 25 jts 8 5/8" 24# J-55 8RD ST&C csg, set @ 1002'. Cemented w/ 350 sx lite "C" + 250 sx class "C". 76 sx cmt returned to surface. woc ? Drid 7 7/8" hole and reached TD 2300' on 3/16/97 at 1650 hrs. Schlumberger ran LDT/CNL/DLL/MSFG/GR logs. Ran 53 jts 5 1/2" 15.5# J-55 8RD csg, set @ 2299'. Cemented w/ 375 sx class "H". 38 sx cmt returned to surface.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TYPE OR PRINT NAME

Tonja Rutelonis

TITLE ENGINEERING TECHNICIAN

TELEPHONE NO. (405) 235-3611

Approved by

DATE

1-9-9-8

Conditions of approval, if anyi 4 1