DEPARTMENT OF MANAGEMENT					5. LEASE DESIGNATION AND BERIAL NO. NM-0437522	
	LICATION FO	OR PERMIT TO	DRILL OR DEEPEN		6. IF INDIAN, ALLOTTE	OR TRIBE NAME
	DRILL 🖾	DEEPEN			7. UNIT AGREEMENT N	AMB
OIL	GAS (73)					
NAME OF OPERATO		HER			6. FARM OR LEASE NAME WE East Turkey	Track
MYCO INDUS	TRIES, INC.) .	5445		Federal Com. 9. ARIWELLNO.	#3 8252
ADDRESS AND TELEPHON					30-115-	30264
105 South	Fourth Street	., Artesia, New	Mexico 88210(505)7 ith any State requirements.*)	48-1471	10. FIELD AND POOL, O Turkey Track	MOTTOW
ar surrace	and 1980' FEI		North Gas 11. SEC., T., B., M., OR BLK.			
At proposed prod.			AND SURVEY OR AREA			
Same					Section 26,	T18 D- R29E
		M NEAREST TOWN OR PO	st office. Loco Hills, New Mex	i co	12. COUNTY OR PARISH	13. BTATE
. DISTANCE FROM P	BOPUSED*		LOCO HILLS, NEW MEX	I	Eddy County	New Mexico
LOCATION TO NEA PROPERTY OR LEA (A)so to present	SE LINE, FT.	1732'	320	TO TH	ACRES ASSIGNED	
DISTANCE FROM	drig. unit line, if any BOFOSED LOCATION®		19. PROPOSED DEPTH	20. ROTAR	T OB CABLE TOOLS	<u> </u>
TO NEAREST WELL, DRILLING, COMPLETED, OR APPLIED FOR, ON THIS LEASE, FT. L. ELEVATIONS (Show whether DF, RT, GR, etc.)			11 0001		Rotary	
3431' GR	whether DF, RT, GR.	CAPITAN CON	TROLLED WATER	Agini	22. APPROX. DATE WO	BE WILL START*
					ASAP	
			ING AND CEMENTING PROGR	RAM		fost ID-1
17 1/2"	GRADE, SIZE OF CAS				QUANTITY OF CEMEN	
17 1/2 12 1/4"	<u> </u>		<u> </u>		VICESS Circulated HPI+ boc	
7 7/8"	5 1/2"		11800'		1200 sx Circulated 3000 sx at least 600'	
	I	ļ	·			Wolfcamp
				abo	ove the top of	norreamp.
Myco Indust Will drill	ries, Inc. pr	oposes to drill	and test the Morr	ow and ir	termediate for	rmationa
WITT GLITT	a 12 1/4" nol	e to approximat	ely 4000' (base Sa	ow and ir n Andres)	ntermediate for before running	rmations.
intermediat st-approxim	a 12 1/4" nol e casing. If a tely-4000'.	e to approximat -water_flow_is_ If no San Andr	cely 4000' (base Sa <u>encountered in the</u> ces water flow is e	ow and ir n Andres) <u>San Andr</u> ncountere	termediate fo: before runnin cos will set 8	rmations. ng 8 5/8" -5/8" thru S
intermediat at-approxim 3200'. Cem	a 12 1/4" hoi e casing. If ately 4000'. ent will be c	e to approximat -water-flow_is If no San Andr irculated on th	cely 4000' (base Sa <u>encountered in the</u> ces water flow is e ne 8 5/8" casing ei	ow and ir n Andres) <u>San Andr</u> ncountere ther case	termediate fo: before runnin cos will set 8 ed will set 8	rmations. ng 8 5/8" - <u>5/8" thru s</u> 5/8" casing
intermediat at-approxim 3200'. Cem production	a 12 1/4" hol e casing. If ately 4000'- ent will be c casing will b	e to approximat water flow is If no San Andr irculated on th e set and cemen	cely 4000' (base Sa <u>encountered in the</u> ces water flow is e ne 8 5/8" casing ei nted at least 600'	ow and ir n Andres) <u>San Andr</u> ncountere ther case above the	termediate fo: before runnin cos will set 8 ed will set 8 s be. If commerc:	rmations. ng 8 5/8" -5/8" thru s 5/8" casing ial, of Wolfgar
intermediat st-approxim 3200'. Cem production	a 12 1/4" hol e casing. If ately 4000'- ent will be c casing will b	e to approximat water flow is If no San Andr irculated on th e set and cemen	cely 4000' (base Sa <u>encountered in the</u> ces water flow is e ne 8 5/8" casing ei	ow and ir n Andres) <u>San Andr</u> ncountere ther case above the	termediate fo: before runnin cos will set 8 ed will set 8 e. If commerc: Wolfcamp (top tion as warran	rmations. ng 8 5/8" -5/8" thru 5 5/8" casing ial, p of Wolfcam nted.
intermediat at approxim 3200'. Cem production 3600'). Pr	e casing. If ately 4000'. ent will be c casing will b oduction will	e to approximat water flow is If no San Andr irculated on th e set and cemen be achieved wi	tely 4000' (base Sa encountered in the res water flow is e ne 8 5/8" casing ei nted at least 600' th perforations an	ow and ir n Andres) <u>San Andr</u> ncountere ther case above the d stimula	termediate for before running will set 8 d will set 8 . If commerce Wolfcamp (top tion as warrang 	rmations. ng 8 5/8" -5/8" thru 5 5/8" casing ial, p of Wolfcam hted. BJECT TO
MILL GITTI intermediat at approxim 3200'. Cem production 3600'). Pro MUD PROGRAM	e casing. If ately 4000'- ent will be c casing will b oduction will : FW to 350'	e to approximat water flow is If no San Andr irculated on th e set and cemen be achieved wi ; Brine to 4000	tely 4000' (base Sa encountered in the res water flow is e he 8 5/8" casing ei hted at least 600' th perforations an 0'; SW Gel/Starch t	ow and ir n Andres) <u>San Andr</u> ncountere ther case above the d stimula o TD.	termediate fo: before runnin bed will set 8 d will set 8	rmations. ng 8 5/8" -5/8" casing ial, o of Wolfcam hted. BJECT TO UIREMENTS
intermediat at approxim 3200'. Cem production 3600'). Pr	e casing. e casing. ent will be c casing will be oduction will : FW to 350' M: BOPE's will	e to approximat water flow is If no San Andr irculated on th e set and cemen be achieved wi ; Brine to 4000 ll be installed	tely 4000' (base Sa encountered in the res water flow is e ne 8 5/8" casing ei nted at least 600' th perforations an	ow and ir n Andres) <u>San Andr</u> ncountere ther case above the d stimula o TD.	termediate for before running will set 8 d will set 8 . If commerce Wolfcamp (top tion as warran 	rmations. ng 8 5/8" -5/8" casing ial, o of Wolfcam hted. BJECT TO UIREMENTS
MILL GITTI intermediat at approxim 3200'. Cem production 3600'). Pro MUD PROGRAM	e casing. If ately 4000'- ent will be c casing will b oduction will : FW to 350'	e to approximat water flow is If no San Andr irculated on th e set and cemen be achieved wi ; Brine to 4000 ll be installed	tely 4000' (base Sa encountered in the res water flow is e he 8 5/8" casing ei hted at least 600' th perforations an 0'; SW Gel/Starch t	ow and ir n Andres) <u>San Andr</u> ncountere ther case above the d stimula o TD.	termediate fo: before runnin bed will set 8 d will set 8	rmations. ng 8 5/8" -5/8" casing ial, o of Wolfcam hted. BJECT TO UIREMENTS
Mill Gilli intermediat at approxim 3200'. Cem production 3600'). Pro MUD PROGRAM 30PE PROGRAM	e casing. e casing. ent will be c casing will be oduction will : FW to 350' M: BOPE's will operation	e to approximat water flow is If no San Andr irculated on th e set and cemen be achieved wi ; Brine to 4000 ll be installed al.	tely 4000' (base Sa encountered in the res water flow is e the 8 5/8" casing ei ated at least 600' th perforations an 0'; SW Gel/Starch to 1 on the 13 3/8" ca	ow and ir n Andres) <u>San Andr</u> ncountere ther case above the above the d stimula o TD. sing and	termediate for before running will set 0 ad will set 8 a. If commerce Wolfcamp (top tion as warran PROVAL SU GENERAL REQ CENERAL REQ CENERAL REQ	rmations. ng 8 5/8" <u>5/8" thru s</u> 5/8" casing ial, o of Wolfcam nted. BJECT FO UIREMENTS JLATIONS
NO WAT	e casing. If ately 4000'. ent will be c casing will be oduction will : FW to 350' M: BOPE's will operation	e to approximat water flow is If no San Andr irculated on th e set and cemen be achieved wi ; Brine to 4000 Il be installed al. TERED IN 0	FFSETS PER NEL	ow and ir n Andres) <u>San Andr</u> ncountere ther case above the d stimula o TD. sing and Sov Mu	termediate for before running will set 8 d will set 8 . If commerce Wolfcamp (top tion as warran 	rmations. ng 8 5/8" <u>5/8" thru 5</u> 5/8" casing ial, o of Wolfcam hted. BJECT FO UIREMENTS. JLATIONS
MILL GITTI intermediat at approxim 3200'. Cem production 3600'). Pr MUD PROGRAM BOPE PROGRAM	A 12 174" hol e casing. If ately 4000'. ent will be c casing will be oduction will : FW to 350' A: BOPE's will operations ER ENCOUN RUBE PROPOSED PROGR	e to approximat water flow is If no San Andr irculated on th e set and cemen be achieved wi ; Brine to 4000 Il be installed al. TERED /N O	tely 4000' (base Sa encountered in the ces water flow is e the 8 5/8" casing ei the at least 600' th perforations an 0'; SW Gel/Starch to 1 on the 13 3/8" ca FFSETS PER NEL sive data on present productive and	ow and ir n Andres) <u>San Andr</u> ncountere ther case above the d stimula o TD. sing and Sov Mu	termediate for before running will set 8 d will set 8 Wolfcamp (top tion as warran PROVAL SU FNERAL REQ DEFCIAL SIP tested baily	rmations. ng 8 5/8" <u>5/8" thrus</u> 5/8" casing ial, o of Wolfcam hted. BJECT TO UIREMENTS JLATIONS
MILL GITTI intermediat at approxim 3200'. Cem production 3600'). Pr MUD PROGRAM BOPE PROGRAM	A 12 174" hol e casing. If ately 4000'. ent will be c casing will be oduction will : FW to 350' A: BOPE's will operations ER ENCOUN RUBE PROPOSED PROGR	e to approximat water flow is If no San Andr irculated on the e set and cemen be achieved wi ; Brine to 4000 11 be installed al. TERED IN O AM: If proposal is to deepen, be locations and measured and the be achieved wi	tely 4000' (base Sa encountered in the res water flow is e he 8 5/8" casing ei hted at least 600' th perforations an 0'; SW Gel/Starch to 1 on the 13 3/8" ca FFSETS PER NEZ give data on present productive zon rue vertical depths. Give blowout pre-	ow and ir n Andres) <u>San Andr</u> ncountere ther case above the d stimula o TD. sing and SON Mu e and proposed n venter program, if	termediate for before running will set 8 d will set 8 d w	rmations. ng 8 5/8" 5/8" thru 5 5/8" casing ial, o of Wolfcam hted. BJECT TO UIREMENTS JLATIONS
NO WAT	A 12 174" hol e casing. If ately 4000'. ent will be c casing will be oduction will : FW to 350' A: BOPE's will operations ER ENCOUN RUBE PROPOSED PROGR	e to approximat water flow is If no San Andr irculated on the e set and cemen be achieved wi ; Brine to 4000 11 be installed al. TERED IN O AM: If proposal is to deepen, be locations and measured and the be achieved wi	tely 4000' (base Sa encountered in the res water flow is e he 8 5/8" casing ei hted at least 600' th perforations an 0'; SW Gel/Starch to 1 on the 13 3/8" ca FFSETS PER NEZ give data on present productive zon rue vertical depths. Give blowout pre-	ow and ir n Andres) <u>San Andr</u> ncountere ther case above the d stimula o TD. sing and SON Mu e and proposed n venter program, if	termediate for before running will set 8 d will set 8 d w	rmations. ng 8 5/8" 5/8" thru 5 5/8" casing ial, o of Wolfcam nted. BJECT FO UIREMENTS JLATIONS CLAS Poposal is to drill or
NO WAT BOPE PROGRAM BOPE PROGRAM BOPE PROGRAM BOPE PROGRAM BOPE SPACE DESC Endirectionally, give p	A 12 174" hol e casing. If ately 4000'- ent will be c. casing will be oduction will : FW to 350' M: BOPE's will operation: ER ENCOUN RIBE PROPOSED PROGREE ENTITIENT data on subsurface	e to approximat water flow is If no San Andr irculated on the e set and cemen be achieved wi ; Brine to 4000 11 be installed al. TERED /N Of CAM: If proposal is to deepen, clocations and measured and the May TIM	tely 4000' (base Sa encountered in the ces water flow is e the 8 5/8" casing ei the at least 600' th perforations an 0'; SW Gel/Starch to 1 on the 13 3/8" ca FFSETS PER NEL sive data on present productive and	ow and ir n Andres) <u>San Andr</u> ncountere ther case above the d stimula o TD. sing and SON Mu e and proposed n venter program, if	termediate for before running will set 8 d will set 8 d w	rmations. ng 8 5/8" 5/8" thru 5 5/8" casing ial, o of Wolfcam nted. BJECT FO UIREMENTS JLATIONS CLAS Poposal is to drill or
MUD PROGRAM MUD PROGRAM BOPE PROGRAM BOPE PROGRAM NO WAR BOVE SPACE DESC SIGNED (This space for F	a 12 174" hol e casing. If ately 4000' ent will be c casing will be oduction will : FW to 350' M: BOPE's will operations ER ENCOUN RIBE PROPOSED PROGR Extinent data on subsurface M. R. Y enteral or State office u	e to approximat water flow is If no San Andr irculated on the e set and cemen be achieved wi ; Brine to 4000 Il be installed al. TERED /N Of CAM: If proposal is to deepen, clocations and measured and the May TIME TIME	tely 4000' (base Sa encountered in the res water flow is e he 8 5/8" casing ei hted at least 600' th perforations an 0'; SW Gel/Starch to a on the 13 3/8" ca FFSETS PER NEL give data on present productive zon mue vertical depths. Give blowout pre-	ow and ir n Andres) <u>San Andr</u> ncountere ther case above the d stimula o TD. sing and SON Mu e and proposed n venter program, if	termediate for before running will set 8 d will set 8 d w	rmations. ng 8 5/8" <u>5/8" thru S</u> 5/8" casing ial, o of Wolfcam nted. BJECT FO UIREMENTS JLATIONS CAS Poposal is to drill or
MUD PROGRAM MUD PROGRAM BOPE PROGRAM BOPE PROGRAM NO WAT BOVE SPACE DESC SIGNED (This space for F PERMIT NO.	A 12 1/4" hol e casing. If ately 4000' ent will be c casing will be oduction will : FW to 350' A: BOPE's will operations ERENCOUN RIBE PROPOSED PROGR Extinent data on subsurface for R. Y	e to approximat water flow is If no San Andr irculated on th e set and cemen be achieved wi ; Brine to 4000 Il be installed al. TERED IN O May TH Bee)	tely 4000' (base Sa encountered in the res water flow is e he 8 5/8" casing ei hted at least 600' th perforations an 0'; SW Gel/Starch to 1 on the 13 3/8" ca FFSETS PER NEZ give data on present productive zon rue vertical depths. Give blowout pre-	ow and ir n Andres) San Andr ncountere ther case above the d stimula o TD. sing and SON M4 e and proposed n venter program, if	termediate for before runnin termediate for before runnin termediate of ad will set 8 s. If commerce Wolfcamp (top tion as warran PROVAL SUI FNERAL REQ tested bally tested bally	rmations. ng 8 5/8" <u>5/8" thru S</u> 5/8" casing ial, p of Wolfcam nted. BJECT FO UIREMENTS A JUATIONS CASE 15, 1998

*See Instructions On Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.