DEVON ENERGY CORPORATION WELLBORE SCHEMATIC

| WELL NAME: Ma | nn 3 Federal #1 | FIELD: Red Lake (Q-GB-SA) | | | | |
|----------------------------|--|---|------------------------|-------------------|---------------------|---------------|
| LOCATION: Sect 3-T18S-R27E | | | COUNTY: Eddy STATE: NM | | | STATE: NM |
| ELEVATION: GL=3572' | | | SPUD DATE: | 5/29/01 | COMP DATE: | 11/15/01 |
| API#: 30-015-3041 | | DATE: 01/23/02 | | | | |
| TUBULARS | DEPTH | SIZE | WEIGHT | GRADE | THREAD | HOLE SIZE |
| CASING: | 0 - 1315' | 8 5/8" | 24# | J-55 | | 12 1/2" |
| CASING: | 0 - 3625' | 5 1/2" | 15.5# | J-55 | | 7 7/8" |
| CASING: | | | | | | |
| CASING: | ~ | | | | | |
| TUBING: | 0 - 2766' | 2 7/8" | | | | |
| CURRENT PROPOSED | | | | | | |
| | 8 5/8" casing set @1,315' cmt Lead w/415 sx tail 200 sx circulated 75sx to pit Upper San Andres Perforations: 2080' - 2330' (34 holes) 2 7/8" tbg w/SN @2766' Low San Andres Perforations: 2698' - 2777' (30 holes) CIBP @ 3035' | | | | | |
| | | | | | | |
| Yeso Perforations: | | | | | | |
| | | 3120' - 3376' (3 | 5 holes) | | | |
| | | PBTD @ 3,577 5 1/2" casing, s TD @ 3,630' | ' et @3625' cmt Lea | d w/170 sx tail w | v/525 sx circulated | I 72sx to pit |
| | | | | | | |
| | | | | | | |

IMDM GVAL TO UNAPHUB FORTO LIEWROR

00:01 HA 88 KAL SOOS

BECEINED