~c. m 3160-5 (June 1990)

Approved by

Conditions of approval, if any:

## UNITED STATES DEPARTME OF THE INTERIOR BUREAU OF LAND MANAGEMENT

Cons.

N.M. DIV-Dist. 2FORM APPROVED

Budget Bureau No. 1004-0135

0/5/

1301 W. Grand Avenujes March 31, 1993

Soliciase Designation and Serial No. SUNDRY NOTICES AND REPORTS ON WELLS Artesia, NM Do not use this form for proposals to drill or to deepen or reentry to a different reservoir Use "APPLICATION FOR PERMIT—" for such proposals 6. If Indian, Allottee or Tribe Name 1617 18 19 20 27 SUBMIT IN TRIPLICATE 7. If Unit or CA, Agreement Designation Type of Well ☐ Gas [3 Oil Well 8. Well Name and No. 2. Name of Operator 0.13 **DEVON ENERGY PRODUCTION COMPANY, LP.** Mann 3 Federal #1 9. API Well No. 3. Address and Telephone No. 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 23102 (405) 235-3611 30-015-30410 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage. Sec., T., R., M., or Survey Description) Red Lake; (Q -GB-SA) 2:178 FSL & 330' FWL, Section 3 -18S, -27E, Unit "L" 11. County or Parish, State Eddy County, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION TYPE OF SUBMISSION Notice of Intent Change of Plans Abandonment Recompletion New Construction Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Altering Casing Final Abandonment Notice Conversion to Injection Other Perf & Acidize San Andres Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\* 11/12/01 TOH w/ rods & pump. ND wellhead, NU BOP. TOH w/ tbg. PU CIBP & TIH on tbg, set CIBP @ ±3050'. Test CIBP to 1000 psi. Perforate Lower San Andres @ 2698'-2777' 1 JSPF for a total of 30 holes (.40"EHD). Acidize Lower San Andres 2698'-2777' w/1500 gals 15% NE-FE 11/13/01 Frac w/90,500 gals fresh water + 58,000# 20/40 Brady sand + 12,750# 16/30 curable resin coated sand. TIH w/ RBP & set @ ±2470'. Test RBP to 4000 psi. Perforate Upper San Andres @ 2080'-2330' 1 JSPF for a total of 34 holes (.40" EHD). Acidize Upper San Andres 2080'-2330' w/2500 gals 15% Ne-FE and Frac w/121,500 gals fresh water + 73,500# 20/40 Brady sand + 16,500#16/30 curable resin coated. ACCEPTED FOR RECORD 11/14/01 Retrieve RBP. 11/15/01 RIH w/pump and rods respace well hung well on RDMO, SN @ 2766' LES BABYAK PETROLEUM ENGMEER 14. I hereby certify that the foregoing is true and gorrect Karen A. Cottom Date January 23, 2002 Engineering Technician (This space for Federal or State office use)

EUREN, OFTAND MONT.

92:9 NA 85 MAL 5035

BECEINED