INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE Southeastern New Mexico Northeastern New Mexico

T. Anhy		T. Canyon	9324*	T. Ojo Alamo	Т	. Penn. "B"
T. Salt		T. Strawn		T. Kirtland-Fruitland	1 T	. Penn. "C"
B. Salt		T. Atoka		T. Pictured Cliffs	Т	. Penn. "D"
T. Yates	684*	T. Miss		T. Cliff House	Т	. Leadville
T. 7 Rivers		T. Devonian		T. Menefee	Т	. Madison
T. Queen	<u>1805'</u>	T. Silurian		T. Point Lookout	T	. Elbert
T. Grayburg		T. Montoya		T. Mancos	T	. McCracken
T. San Andres	2288'	T. Simpson		T. Gallup	T	. Ignacio Otzte
T. Glorieta		Т. МсКее			Т	. Granite
T. Paddock		T. Ellenburger		T. Dakota	Τ	;
T. Blinebry		T. Gr. Wash		T. Morrison	1	•
T. Tubb		T. Delaware Sand		T. Todilto	Т	•
T. Drinkard		T. Bone Springs	<u> </u>	T. Entrada		•
T. Abo		T.2nd BSGL Sand	6750 °	T. Wingate	Т	•
T. Wolfcamp	8076	T.3rd BSGL Sand	7814*	T. Chinle	Т	•
T. Penn		T.Morrow	10.334	T. Permain	Т	
T. Cisco (Bough C)	8902	T.Lower Morrow	10.706'	T. Penn "A"	Τ	·
		OIL OF	GAS SAN	IDS OR ZONES		
No. 1, from		to		No. 3, from		to
No. 2, from		to		No. 4, from		to
				ATER SANDS		
Include data on rate of wa	ter inflo	w and elevation to wh	ich water ros	se in hole.		
No. 1, from	to			fe	et	
No. 2, from		to		fe	et	
No. 3. from		to		fe	et	

LITHOLOGY RECORD (Attach additional sheet if necessary)

			· · · · · · · · · · · · · · · · · · ·				· · · · · · · · · · · · · · · · · · ·
From	То	Thickness in Feet	Lithology	From	То	Thickness in Feet	Lithology
			SIDE TRACK FORMATION TOPS				
		684'	Yates				
		1805'	Queen				
		2288*	San Andres				
		3727*					
		6750	2nd BSGL Sand				
		7812*	3rd BSGL Sand				
		8076*	Wolfcamp				
		8896*	Cisco				
		9324*	Canyon				
		9495'	Strawn				
		10,113'	Atoka				
		10,330'	Morrow				
		10,691'	Lower Morrow				
	1	l			1	l	I