Form 3160-5 (June 1990)

UNATED STATES DEPARTME OF THE INTERIOR BUREAU OF LAND MANAGEMENT

N. DIV-Dist. 2 CIST 1301 W. Grand Avenue Artesia, NM 88294 Preau No. 1004-0135 Expires March 31 1993

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals		5. Lease Designation and Serial No. LC-061783-A 6. If Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE		n/a
1. Type of Well Oil Gas Well Other		7. If Unit or CA, Agreement Designation n/a
2. Name of Operator DEVON ENERGY PRODUCTION COMPANY, LP.		8. Well Name and No. Windfohr 4 Federal #7
3. Address and Telephone No. 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405) 235-3611		9. API Well No. 30-015-30460
4. Location of Well (Footage. Sec., T., R., M., or Survey Description) 1140' FSL & 1105' FEL, Sect 4-18S-27E, Unit "P"		Red Lake; (Q-GB-SA) 11. County or Parish, State Eddy County, New Mexico
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPO	ORT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
 Notice of Intent Subsequent Report Final Abandonment Notice 	Abandonment ☐ Recompletion ☐ Plugging Back ☐ Casing Repair ☐ Altering Casing ☐ Other Perf & Acidize San Andres	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well
subsurface locations and measured and true vertical depths		Completion or Recompletion Report and Log form.) any proposed work. If well is directionally drilled, give
pump. ND wellhead, NU BOP. TOH Perforate Lower San Andres @ 2675'-2675'-2770' w/1500 gals 15% NE-FE acurable resin coated sand. TIH w/ RBF 2306' 1 JSPF for a total of 30 holes (.4 Frac w/121,500 gals fresh water + 73,5 Run pumping equipment & pump test to	.P. plans to perforate and stimulate the San Aw/thg. PU CIBP & TIH on the set CIBP @ : 2770' 1 JSPF for a total of 22 holes (.40"EHD and Frac w/90,500 gals fresh water + 58,000# 2 & set @ ±2400'. Test RBP to 1000 psi. Per 0" EHD). Acidize Upper San Andres 2080'-2 00# 20/40 Brady sand + 16,500#16/30 curable antil production stabilizes. After well pumps eso (currently in the process of filing a downly	±2950'. Test CIBP to 1000 psi.). Acidize Lower San Andres 20/40 Brady sand + 12,750# 16/30 forate Upper San Andres @ 2080'- 306' w/2500 gals 15% Ne-FE and e resin coated. Retrieve RBP. down, drill out CIBP & commingle
14. I hereby certify that the foregoing is true and correct Signed	Karen A. Cottom Title Engineering Technician	Date August 7., 2001
(This space for Federal or State office use) Approved by	77 PETROLEUM ENGINEE	AUG 17 2001
Conditions of approval, if any: (ORIG. SGD.) ALEXIS C. S	SWOBODA	

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations to any matter within its jurisdiction.