Form ?160-5 (June 1990)

## UN TO STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Division APPROVED

811 S. 1st Stroot

Budget Bureau No. 1004-0135

dyr
-----

811 S. 1st Street Expires March 31, 1993 SUNDRY NOTICES AND REPORTS ON WELLSArtesia ease Designation and Serial No. -2834 -061783-A Do not use this form for proposals to drill or to deepen or reentry to a different Use "APPLICATION FCR PERMIT—" for such proposals 6. If Indian, Allottee or Tribe Name SUBMIT IN TRIPLICATE 7. If Unit or CA, Agreement Designation 1. Type of Well Gas Well ⊠ O.I Well Other 8. Well Name and No. 2. Name of Operator DEVON ENERGY PRODUCTION COMPANY, L.P. Windfohr 4 Federal #1 9. API Well No. 3. Address and Telephone No 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 30-015-30467 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Red Lake: Glorieta-Yeso 2185' FSL & 974' FEL, Section 4-18S-27E, Unit "I" 11. County or Parish, State Eddy County, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION TYPE OF SUBMISSION Change of Plans Abandonment Notice of Intent **New Construction** Recompletion Non-Routine Fracturing Subsequent Report Plugging Back Water Shut-Off Casing Repair Conversion to Injection Final Abandonment Notice Altering Casing Other Spud, csg string, TD Dispose Water (Note: Report results of multiple completion on Well 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\* Spud well on 10/22/00 at 1930 hrs and drld an 11" hole to 1165'. On 10/24/00 ran 26 jts 8 5/8" 24# J-55 8RD STC csg, set @ 1155'; cemented w/ 100 sx class "H" + 200 sx 35:65 POZ + 200 sx class "C". Ran steel tape outside 8-5/8" csg. Tagged cmt @ 80'. Received permission from BLM to fill w/ Ready Mix. Topped out w/ 6-1/2 cu. ft. Ready Mix. Drld 7 7/8" hole and reached TD 3800' on 10/29/00 at 1300 hrs. Schlumberger ran Platform Express Three Detector Litho-Density CNL/GR and Azimuthal Laterolog Micro-CFL/GR. Ran 88 jts 5 1/2" 15.5# J-55 LTC.8RD csg, set @ 3794'. Cemented w/ 275 sx 35:65:6 C + 600 sx 50:50 C. Estimated top of cement 1002 n FOR RECORD MOV 15 2000 Released rig at 2400 hrs 10/31/00. WOCU. 14. I hereby certify that the foregoing is true and correct Tonja Rutelonis Date 11/7/00 Engineering Technician (This space for Federal or State office use) Conditions of approval, if any: