Windfohr 4 Federal #1, 30-015-30467, LC-061783-A

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.
Premier sand	1490'	1530'	sandstone
San Andres	1530'	2903'	dolomite
Glorieta	2903'	3003'	sd & dolomite
Yeso	3022'	3800'	dolomite

DEPTH	ACID, SHOT, FRACTURE, CEMEMNT SQUEEZE, ETC.. (continued from the front)
3022' - 3312'	45,000 gal FW & 36,000 gal crosslink gelled fresh wtr & 99,000 # 20/40 Brady sd & 22,000# 16/30 CRC sd
1833' - 2254'	100,000 gal FW & 20# linear gel wtr & 40,000# 20/40 Brady sd
2656' - 2746'	70,000 gal FW & 20# linear gel wtr & 25,000# 20/40 Brady sd & 15,000 CRC sd

38. GEOLOGIC MARKERS

NAME	TOP MEAS. DEPTH	TOP TRUE VERT. DEPTH
Bowers	673'	
Queen	870'	
Grayburg	1226'	
Permier	1490'	
San Andres	1530'	
Glorieta	2903'	
Yeso	3003'	