Form 3160-5 (June 1990)

## UNITED STATES DEPARTMEL OF THE INTERIOR BUREAU OF LAND MANAGEMENT

. Cons.
N.M. DIV-Dist. 20RM APPROVED
1301 W. Grand AVER USB Harch 31, 1993

Do not use this form for proposals to drill o	AND REPORTS ON WELLS ARESIA, r to deepen or reentry to a different reservoir.  R PERMIT—" for such proposals	LC-061783-A  6. If Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE		7. If Unit or CA, Agreement Designation
1. Type of Well  Oil Well  Gas Well  Other	101172137478	8. Well Name and No.
2. Name of Operator DEVON ENERGY PRODUCTION COMPANY, LP. Windfohr 4 Federal #4		Windfohr 4 Federal #4
3. Address and Telephone No.  20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102, (405) 235-3611 30-015-30474		
4. Location of Well (Footage. Sec., T., R., M., or Survey 1650' FSL & 2200' FEL, Sect 4-18S, 27e, U	Description)	Red Lake (Q-GB-SA)  11. County or Parish, State  Eddy County, NM
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA		
TYPE OF SUBMISSION	TYPE OF ACTIO	N
Notice of Intent	Abandonment Recompletion	Change of Plans  New Construction  Non-Routine Fracturing
Subsequent Report	Plugging Back Casing Repair	Water Shut-Off
Final Abandonment Notice	Altering Casing Other Perf & Acidize San Andres	Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*		
8/6/01 TOH w/ rods & pump. ND wellhead, NU BOP. TOH w/ tbg.		
8/7/01 PU CIBP & TIH on tbg, set CIBP @ ±2900'. Test CIBP to 1000 psi. Perforate Lower San Andres @ 2593'-2684' 1 JSPF for a total of 30 holes (.40"EHD). Acidize Lower San Andres 2593'-2684' w/1500 gals 15% NE-FE		
8/8/01 Frac w/90,500 gals fresh water + 58,000# 20/40 Brady sand + 12,750# 16/30 curable resin coated sand. TIH w/ RBP & set @ ±2350'. Test RBP to 1000 psi. Perforate Upper San Andres @ 2057'-2237' 1 JSPF for a total of 23 holes (.40" EHD). Acidize Upper San Andres 2057'-2237' w/2500 gals 15% Ne-FE and Frac w/121,500 gals fresh water + 73,500# 20/40 Brady sand + 16,500#16/30 curable resin coated.  8/9/01 Retrieve RBP.		
8/9/01 Retrieve RBP.		TOR RECORD
8/10/01 TIH w/pump & rods. Hung well on prod. RD (SN @ 2617' w/85 jnts in hole.)		
14. I hereby sertify that the foregoing is true and correct		STUM ENGINEER
Signed Signed Signed	Karen A. Cottom  Title <u>Engineering Technician</u>	Date October 9, 2001
(This space for Federal or State office use)		
Approved byConditions of approval, if any:	Title	Date

BUREAU CHILL OFFICE BUREAU CHILL OFFICE

2001 OCT 12 AM 9: 34

BECEINED