State of New Mexico Er , Minerals and Natural Resources Departmen

DISTRICT

SERVATION DIVISION	U	<u>′ </u>
0 Pacheco St.	WELL API NO.	
o r doness st. nta Fe NM 87505	30 015 30643	

C157	Form C-103 Revised 1-1-89
ELL API NO.	
30 015 30643	

P.O. Box 1980, Hobbs, NM 88240	OIL CONSERVATION	ON DIVISION	V	Ĺ	
2040 Pacheco St.		WELL API NO.			
DISTRICT II	Santa Fe, NM 8	37505	30 015 30643		
P.O. Drawer DD, Artesia, NM 88210			sIndicate Type of Leas		
DISTRICT III				STATE	FEE
1000 Rio Brazos Rd., Aztec, NM 87410			State Oil & Gas Lease	No.	
· · · · · · · · · · · · · · · · · · ·					
SUNDRY NOTICES AND REPORTS ON WELLS		168	iller titt a	-	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"		7Lease Name or Unit A	greement Name		
(FORM C-101) FOR SUCH PROPOSALS.)		010			
Type of Well:			Sand Dunes 36 S	tate Com	
OIL GAS WELL X	OTHER				
₂Name of Operator ✓			«Well No.		
Nearburg Producing Company			1		
, ·	3Address of Operator		Pool name or Wildcat		
4Well Location	Suite 120, Midland, TX 79705 (915)	686-8235	Turkey Track; Mo	orrow, North	
E 4050	Feet From The North	660		\ \ \ \ \ \ - \	
Unit LetterE :1650_	Feet From The North	Line and660	Feet From The _	West	Line
Section 36	Township 18S	Range 29E	NMPM	Eddy	County
Transcript of the second	10 Elevation (Show whether DF	· · · · · ·		The state of the s	County
在《福祉 》(1994年)。4月2日 新疆山田 2月	3,444' GR				12.0
11 Check A	Appropriate Box to Indicate N	ature of Notice. Re	port, or Other Da	ata	
	NTENTION TO:	1			
NOTICE OF II	TENTION TO:	SOBS	SEQUENT REI	PORT OF:	
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK		ALTERING CASING	G
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLING O	PNS.	PLUG AND ANBAN	DONMENT
PULL OR ALTER CASING		CASING TEST AND CEME	CASING TEST AND CEMENT JOB		
OTHER:					∇
OTHER:		OTHER: Intermediate Casing and Cement			A
	ons (Clearly state all pertinent details, and given	e pertinent dates, including es	timated date of starting a	nny proposed	
work) SEE RULE 1103.					
Drilled to 3 206' C&C hole RU	and run 77 jts 8-5/8", 24# & 32#, 、	155, STC casing to 3.20	6' Cement casing	using 900 eye o	ement
plus additives. Circ 150 sxs cmt	to surface. WOC. ND BOPE. Cu	t off wellhead and weld	on wellhead. NU B	BOPE and test.	Ciricin
·					
			19	4	
			<i>j</i> *	₹ .	
			On PEO	1000	
			18/N	C.	
			7975	0	
				1/4	
			4210	e de la	
I hereby certify that the information above	is true and complete to the best of my knowle	edge and belief.			
SIGNATURE SEE	dewart 1	TITLE Regulatory Analyst		DATE 06-29-9	9
TYPE OR PRINT NAME KIM Stewart			1	TELEPHONE NO. (91	5)686-8235

(This space for State Use)

APPROVED BY

Sim W. Gens TITLE District Supervisor

CONDITIONS OF APPROVAL, IF ANY: