Submit 3 Copies to Appropriate District Office	State of New Mexico Energy, Minerals and Natural Resources Department		CIST Form C-103 Revised 1-1-89
<u>DISTRICT I</u> P.O. Box 1980, Hobbs, NM 88240	OIL CONSERVATION DIVISION 2040 Pacheco St.		V WELL API NO. 30-025-
<u>DISTRICT II</u> P.O. Drawer DD, Artesia, NM 88210	Santa Fe, NM 87505		Indicate Type of Lease
<u>DISTRICT III</u> 1000 Rio Brazos Rd., Aztec, NM 87410			•State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" HEALER (FORM C-101) FOR SUCH PROPOSALS.)			Apase Name or Unit Agreement Name Key State
Type of Well: OIL GAS	OTHER		× V
2Name of Operator SDX Resources, Inc.	UTHER		₃₩eli No. 2
Address of Operator PO Box 5061, Midland, TX 79704			Pool name or Wildcat Artesia, QN-GB-SA
4Well Location			
Unit Letter <u>F 1493</u> Feet From The <u>North</u> Line and <u>1716</u> Feet From The <u>West</u> Line			
Section 21 Township 18S Range 28E NMPM Eddy County			
□€levation (Show whether DF, RKB, RT, GR, etc. 3588 GR			
11 Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data			
NOTICE OF INT	NOTICE OF INTENTION TO: SUB		SEQUENT REPORT OF:
			ALTERING CASING
		COMMENCE DRILLING OPNS.	
PULL OR ALTER CASING	CASING TEST AND CEMEN		ENT JOB
OTHER:		OTHER: Change name of well.	
12Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.			
لح Drilled as Key State #1 (located 915' FNL 1615' FWL, Unit C). Drilled 12-1/4" hole to 375'. Ran 370' 8-5/8" 24# csg. Cmt w/325 sx. Circ 100 sx. Drilled 7-7/8" hole to 2850'. Ran 4-1/2" 11.6# - 10.5# csg to 2846'. Cmt w/425 sx Lite & 350 sx C. Discovered survey error before completion. Wellbore is located 1493' FNL 1716' FWL, Unit F. Moved rig over to correct Key State #1			
location and drilled Key State #1 as reported.			
Propose to name this well the Key State #2 and Temporarily Abandon while lease issues are worked out.			
If necessary we will P&A well as follows: Circ hole w/mud laden fluid. Spot 100' plug 2330' - 2430'. (Top SA 2380'). Spot 100' plug across shoe 325' - 425'. Spot 10 sx surface plug & install marker.			
& install marker.			
I hereby certify that the information above is true and complete to the best of my knowledge and belief.			
SIGNATURE Church M	20mganTI	TLE Engineer	DATE 01-19-99
TYPE OR PRINT NAME Chuck Morgan	~		TELEPHONE NO. 915/685-1761
(This space for State Use)			
APPROVED BY	WM T	TLE	DATE