

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-015-30853

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name
Emily ATZ Com

8. Well No.
1

9. Pool name or Wildcat
Richard Knob Morrow

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3533' GR

SUNDRY NOTICES AND REPORTS ON WELLS RECEIVED
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐ GAS WELL ☒ OTHER

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter H : 1980 Feet From The North Line and 660 Feet From The East Line
Section 4 Township 18S Range 25E NMPM Eddy County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: Production casing & cement <input checked="" type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 8650'. Reached TD at 11:15 AM 1-27-2000. Ran 205 joints of 5-1/2" 17# & 15.5# casing as follows: 26 joints of 5-1/2" 17# J-55 sandblasted (1084.28'); 11 joints of 5-1/2" 17# J-55 varnished (461.65'); 17 joints of 5-1/2" 15.5# J-55 sandblasted (726.79'); 143 joints of 5-1/2" 15.5# J-55 varnished (6087.71'); 6 joints of 5-1/2" 17# J-55 varnished (255.90') and 2 joints of 5-1/2" 17# (marker joints) (41.51') (Total 8660.84') of casing set at 8650'. Bottom marker set at 7541'. Top marker set at 6333'. Cemented with 800 sacks of Super H Modified, 5/10% Halad 344, 4/10% CFR3, 5#/sack gilsonite and 1#/sack salt (yield 1.66, weight 13.0). PD 5:15 AM 1-29-2000. Bumped plug to 1900 psi for 2 minutes, OK. WOC. Released rig at 11:00 AM 1-29-2000.

Waiting on completion unit.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE April 28, 2000

TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY TIM W. GUM DISTRICT II SUPERVISOR B6x DATE MAY 15 2000

CONDITIONS OF APPROVAL, IF ANY: