Form 3160-5 (August 1999)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB No. 1004-0135 Expires November 30, 2000

SUNDRY NOTICES AND REPORTS ON WELLS	
Do not use this form for proposals to drill or to re-enter	aı
abandoned well. Use Form 3160-3 (APD) for such proposal	ls.

5. Lease Serial No.

NM-02428

6. If Indian, Allottee or Tribe Name

SUBMIT IN TRIPL	100=== 01 1 1							
	ICATE - Other Instru	ctic	ons on reverse	side	,	7. If Unit	or CA	/Agreement, Name and/or No.
1. Type of Well								
Oil Well A Gas Well C	Other					8. Well N	lame a	nd No.
2. Name of Operator						Cabez	a Al	JD Federal Com #1
Yates Petroleum Cor	poration		_			9. API W		
3a. Address					code)	30-015-31039		
105 S. 4th St Ar	tesia, NM 88210		505-748-147	71		10. Field a	nd Po	ol, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)						Em	pire	Morrow, South
1060' FNL & 660' FWL of Section 10-T18S-R29E (Unit D, NWNW)					NWNW)	11. County	or Pa	rish, State
1000 1112 0 000 111			·	-				
							Ec	idy Co., NM
12. CHECK APPR	OPRIATE BOX(ES) TO	) IN	DICATE NATUR	RE O	F NOTICE, RI	EPORT, O	R O	THER DATA
TYPE OF SUBMISSION	TYPE OF ACTION							
	Acidize		Deepen		Production (Start,	Resume)		Water Shut-Off
Notice of Intent	Alter Casing	$\bar{\Box}$	Fracture Treat		Reclamation			Well Integrity
	Casing Repair	$\bar{\Box}$	New Construction		Recomplete		X	Other Intermediate
Subsequent Report	Change Plans	$\bar{\Box}$	Plug and Abandon	$\overline{\Box}$	Temporarily Aba	ındon		casing & cement
Final Abandonment Notice	Convert to Injection	$\overline{\Box}$	Plug Back	$\overline{\Box}$	Water Disposal			<u> </u>
13. Describe Proposed or Completed O		_			•			

determined that the site is ready for final inspection.)

TD 3007'. Reached TD at 6:30 PM 4-24-2000. Ran 68 joints of 8-5/8" 32# J-55 (3013.34') of casing set at 3007'. Regular guide shoe set at 3006'. Float collar set at 2961'. Cemented with 950 sacks Interfill C and 1/4#/sack flocele (yield 2.46, weight 11.9). Tailed in with 250 sacks "C" and 2% CaCl2 (yield 1.32, weight 14.8). PD 6:45 AM 4-25-2000. Bumped plug to 1100 psi, OK. Circulated 168 sacks. WOC. Nippled up and tested to 5000 psi for 15 minutes, OK. Drilled out at 6:00 pM 4-26-2000. WOC 35 hours and 15 minutes. Reduced hole to 7-7/8". Resumed drilling. NOTE: Notified Duncan w/BLM-Carlsbad of

casing and cement - will not witness.

/	3293031-123	
372	<b>Å</b>	25
27	AUS 2000	189
3242	RECEIVED	101
15	1	17

14. I hereby certify that the foregoing is true and correct Name (Printed/Typed)

Rustv K

E6181 51 31 31

Operations Technician

Date August 31, 2000

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

\_\_\_\_

Date

Office

Title