

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

DO NOT WRITE IN THIS SPACE
(Other instructions on reverse side)

FORM APPROVED
OMB NO. 1004-0136
Expires: February 28, 1995

APPLICATION FOR PERMIT TO DRILL OR DEEPEN

5. LEASE DESIGNATION AND SERIAL NO.
LC-029415-B A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
----- 25700

8. FARM OR LEASE NAME, WELL NO.
PUCKETT "A" W.H. # 2

9. API WELL NO.
30-015-31082

10. FIELD AND POOL, OR WILDCAT
MALJAMAR-GRAYBURG, SAN ANDRES

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
SEC. 24 T17S-R31E

12. COUNTY OR PARISH 13. STATE
EDDY CO. NEW MEXICO

1a. TYPE OF WORK
DRILL ☒ DEEPEN ☐

b. TYPE OF WELL
OIL WELL ☒ GAS WELL ☐ OTHER ☐ SINGLE ZONE ☒ MULTIPLE ZONE ☐

2. NAME OF OPERATOR
W.A. & E.R. HUDSON, INC. (JON B. SMITH (505-676-2266) 25111

3. ADDRESS AND TELEPHONE NO.
616 TEXAS STREET, FIRT WORTH TEXAS, 76102 (817-336-7160) 7109

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)
At surface
1330' FNL & 10' FWL SEC. 24 T17S-R31E EDDY CO. NM
At proposed prod. zone SAME Unit E

14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE*
Approximately 10 miles East of Loco Hills New Mexico

15. DISTANCE FROM PROPOSED* LOCATION TO NEAREST PROPERTY OR LEASE LINE, FT. (Also to nearest drig. unit line, if any)
10'

16. NO. OF ACRES IN LEASE
1120±

17. NO. OF ACRES ASSIGNED TO THIS WELL
40

18. DISTANCE FROM PROPOSED LOCATION* TO NEAREST WELL, DRILLING, COMPLETED, OR APPLIED FOR, ON THIS LEASE, FT.
800'

19. PROPOSED DEPTH
4200'

20. ROTARY OR CABLE TOOLS
ROTARY

21. ELEVATIONS (Show whether DF, RT, GR, etc.)
3888' GR.


22. APPROX. DATE WORK WILL START* WHEN APPROVED

23. PROPOSED CASING AND CEMENTING PROGRAM

SIZE OF HOLE	GRADE SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	QUANTITY OF CEMENT
25"	Conductor	NA	40'	Redi-mix cement to surface
12 1/2"	J-55 8 5/8"	24	500'	500 Sx. cement to surface.
7 7/8"	J-55 5 1/2"	15.5	4200'	750 Sx. circulate cement to surface

1. Drill 25" hole to 40'. Set 40' of 20" conductor pipe and cement to surface with Redi-mix.
2. Drill 12 1/2" hole to 500'. Run and set 500' of 8 5/8" 24# J-55 ST&C casing. Cement with 500 Sx. of Class "C" cement + additives, circulate cement to surface.
3. Drill 7 7/8" hole to 4200'. Run and ste 4200' of 5 1/2" 15.5# J-55 ST&C casing. Cement with 500 Sx. of Halco Light + additives and tail in with 250 Sx. of Class "C" cement + additives, circulate cement to surface.

NSL-



ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen, give data on present productive zone and proposed new productive zone. If proposal is to drill or open directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout prevention program, if any.

SIGNED Joe T. Janica TITLE Agent DATE 03/16/00
(This space for Federal or State office use)

PERMIT NO. _____ APPROVAL DATE _____

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.
CONDITIONS OF APPROVAL, IF ANY:

Assistant Field Manager,
Lands And Minerals

APPROVED BY _____ TITLE _____ DATE APR 2 2000

*See Instructions On Reverse Side

18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

425-

RECEIVED
MAR 17 00
BLM
ROSWELL, NM