

FIELD REPORT FOR CEMENTING OF WELLS

OIL CONSERVATION DIVISION

30-015- 31148

Operator YATES PETROLEUM CORP		Lease TUMBLE DINK "AVK" ST COM		Well # 1	
Location of Well	Unit A	Section 16	Township .18	Range 25	County EDDY
Drilling Contractor PATTERSON RIG #1 NA		Type of Equipment ROTARY			

APPROVED CASING PROGRAM

Expires 5/15/01

* Witness 9 5/8 Cementing

Size of Hole	Size of Casing	Weight per Ft	New or Used	Depth	Sacks Cement
17 1/2	13 3/8	48 #		400'	330 Circ
12 1/4	* 9 5/8	36 #		1300'	650 Circ
8 7/8	7	23 # + 26 #		8800'	450 TOC 4700'

Casing Data:

Surface _____ joints of _____ inch _____ # Grade _____

(Approved) (Rejected) _____

Inspected by _____ date _____

Cementing Program

Size of hole _____ Size of Casing 9 5/8 Sacks cement required _____

Type of Shoe used _____ Float collar used _____ Btm 3 jts welded _____

TD of hole 1300' Set 1304' Feet of 9 5/8 Inch 36 # Grade _____

New-used csg. @ _____ with 200 sacks neat cement around shoe

+ 300 sacks Halliburton Life additives _____

Plug down @ 4:15 (AM) (PM) Date 6-3-00

Cement circulated None No. of Sacks _____

Cemented by _____ Witnessed by _____

Temp. Survey ran @ _____ (AM) (PM) Date 6-3-00 top cement @ 409'

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: ONE inch in two Stages w/ 105 SX CL C w/ 2700 Ctl Circ 5 SX