

UNIT STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Division
811 S. 1st Street
Artesia, NM 88210-2834
FORM APPROVED
Budget Bureau No. 1004-0135
March 31, 1993

C151

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT-" for such proposals

SUBMIT ORIGINAL + 6 COPIES

1. Type of Well ☒ Oil Well ☐ Gas Well ☐ Other
2. Name of Operator
Harvey E. Yates Company
3. Address and Telephone No.
P.O. Box 1933, Roswell, NM 88202
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
1,980' FSL & 1,650' FEL
Unit J, Sec 1, T18S, R31E

5. Lease Designation and Serial No.
NMNM-2537
6. If Indian, Allottee or Tribe Name
7. If Unit or CA, Agreement Designation
8. Well Name and No.
Cholla 1 Fed #1
9. API Well No.
30-015-31187
10. Field and Pool, or Exploratory Area
Tamano Bone Springs
11. County or Parish, State
Eddy County, NM

12. CHECK APPROPRIATE BOX (s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other **Spud/csg/cmt/frac job**
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water
(Note: Report results of multiple completion on Well Completion or Recompletion Report and log form)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If wells directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12/31/00 Spud well @ 11:00 pm.
1/2/01 TD 17 1/2" hole @ 6:00 am.
1/3/01 Ran 20 jts 13 3/8" 48# ST&C H-40 csg. Set @ 900'. Cement w/900 sxs Class "C" w/2% CaCl & 1/4# celloseal. Circulate 250 sxs to pit.
1/7/01 TD 12 1/4" hole @ 8:00 pm. Ran 76 jts 8 5/8" 32# ST&C J-55 csg. Set @ 3,102'.
1/8/01 Cement w/900 sxs 35:65 Poz H + 6% gel + 5# salt & 350 sxs "C" + 2% CaCl & 1/4# CF, did not circulate cement.
1/9/01 Run CBL, TOC @ 1,420'. Perf 8 5/8" csg w/4.60 holes @ 1,414'. Set cement retainer @ 1,298'.
1/10/01 Cemented w/950 sxs H + 9% CD-31. Circulate 250 sxs to pit.

ACCEPTED FOR RECORD
(ORIG. SGD.) DAVID R. GLASS
JAN 31 1993

14. I hereby certify that the foregoing is true and correct

Signed Dianna Rodgers Title **Production Analyst**

Date **24-Jan-01**

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any: