CISF

Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

811 S. IST.

ARTESIA, NM 80210-2024 FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

5. Lease Designation and Serial No. NM 83066

6. If Indian, Allottee or Tribe Name

SUNDRY NOTICES AND REPORTS ON WELLS

	SUBMIT IN TRIP	PLICATE	7. If Unit or CA, Agreement Designatio
I. Type of We Oil Well 2. Name of O	Gas Well Other	# JUL 2020	8. Well Name and No. Crow Flats "34" Federal #1
Mewbourne Oil Company 3. Address and Telephone No. P. O. Box 5270, Hobbs, NM 88241 (505) 393-5905		OCD - ARTESIA	9. API Well No. 30-015-31213 10. Field and Pool, or Exploratory Area
Location of 1060' FS	f Well (Footage, Sec., T., R., M., or Survey Description) SL & 660' FWL S34-T16S-R28E	Co. 195 ¹ 5	S. E. Crow Flats, Morrow 11. County or Parish, State Eddy, NM
	CHECK APPROPRIATE BOX(s) TO IND	ICATE NATURE OF NOTICE, REPORT,	OR OTHER DATA
	TYPE OF SUBMISSION	TYPE OF ACTION	
	Notice of Intent Subsequent Report	Abandonment Recompletion Plugging Back	Change of Plans New Construction Non-Routine Fracturing
	Final Abandonment Notice	Casing Repair Altering Casing Cher Spud, Surface & Inter. Csg	Water Shut-Off Conversion to Injection Dispose Water
directiona	Proposed or Completed Operations (Clearly state all pertine all dilly drilled, give subsurface locations and measured and true	et details, and give pertinent dates, including estimated dat e vertical depths for all markders and zones pertinent to this	(Note Report results of multiple completion on Well Completion or Recompletion Report and Log form.) e of starting any proposed work. If well is s work.)*
3. Describe directiona 7/12/00: 7/13/00:	Spud 17-1/2" hole @ 7:15 am. Drilled 17-1/2" hole to 565'. Ran 12 jts 13-3/ Cemented w/ 320 sx BJ Lite "C" w/ 6% Gel, 2	et details, and give pertinent dates, including estimated date vertical depths for all markders and zones pertinent to this 8" 48#, H-40, ST&C Csg & 1 jt 13-3/8" 54.5#, 2% CaCl2 (yd @ 1.88 cuft/sk @ 12.7 ppg). Ta @ 7:00 pm. Circ 51 sx cmt to pit. WOC 18 hrs	e of starting any proposed work. If well is swork.)* J-55, ST&C Csg. il w/ 200 sx Class
directiona 7/12/00:	Spud 17-1/2" hole @ 7:15 am. Drilled 17-1/2" hole to 565'. Ran 12 jts 13-3/ Cemented w/ 320 sx BJ Lite "C" w/ 6% Gel, 2 "C" w/ 2% CaCl2 (yd 1.34 @ 14.8 ppg). PD Drilled 12-1/4" hole to 2090'. Ran 50 jts 8-5/ 2% CaCl2, 1/4#/sk Cello flake & 5# / sk Gilso	8" 48#, H-40, ST&C Csg & 1 jt 13-3/8" 54.5#, 2% CaCl2 (yd @ 1.88 cuft/sk @ 12.7 ppg). Ta @ 7:00 pm. Circ 51 sx cmt to pit. WOC 18 hrs 8", 32#, J-55, ST&C Csg. Cemented w/ 725 s nite (yd 1.89 @ 12.7 ppg). Tail w/ 200 sx Clas 88 sx cmt to reserve pits. WOC 18 hrs. Tested	e of starting any proposed work. If well is s work.)* J-55, ST&C Csg. il w/ 200 sx Class s. Test csg to 1000 psi. x BJ Lite "C" w/ 6% Gel, s "C" w/ 2% CaCl2
7/12/00: 7/13/00:	Spud 17-1/2" hole @ 7:15 am. Drilled 17-1/2" hole to 565'. Ran 12 jts 13-3/ Cemented w/ 320 sx BJ Lite "C" w/ 6% Gel, 2 "C" w/ 2% CaCl2 (yd 1.34 @ 14.8 ppg). PD Drilled 12-1/4" hole to 2090'. Ran 50 jts 8-5/ 2% CaCl2, 1/4#/sk Cello flake & 5# / sk Gilso (yd 1.34 @ 14.8 ppg) PD @ 12:00 pm. Circle	8" 48#, H-40, ST&C Csg & 1 jt 13-3/8" 54.5#, 2% CaCl2 (yd @ 1.88 cuft/sk @ 12.7 ppg). Ta @ 7:00 pm. Circ 51 sx cmt to pit. WOC 18 hrs 8", 32#, J-55, ST&C Csg. Cemented w/ 725 s nite (yd 1.89 @ 12.7 ppg). Tail w/ 200 sx Clas	e of starting any proposed work. If well is swork.)* J-55, ST&C Csg. il w/ 200 sx Class s. Test csg to 1000 psi. x BJ Lite "C" w/ 6% Gel, s "C" w/ 2% CaCl2 d BOP w/ Safety Test, Inc
directional 7/12/00: 7/13/00: 7/17/00:	Spud 17-1/2" hole @ 7:15 am. Drilled 17-1/2" hole to 565'. Ran 12 jts 13-3/ Cemented w/ 320 sx BJ Lite "C" w/ 6% Gel, 2 "C" w/ 2% CaCl2 (yd 1.34 @ 14.8 ppg). PD Drilled 12-1/4" hole to 2090'. Ran 50 jts 8-5/ 2% CaCl2, 1/4#/sk Cello flake & 5# / sk Gilso (yd 1.34 @ 14.8 ppg) PD @ 12:00 pm. Circ To 3000 psi. (Chart Attached)	8" 48#, H-40, ST&C Csg & 1 jt 13-3/8" 54.5#, 2% CaCl2 (yd @ 1.88 cuft/sk @ 12.7 ppg). Ta @ 7:00 pm. Circ 51 sx cmt to pit. WOC 18 hrs 8", 32#, J-55, ST&C Csg. Cemented w/ 725 s nite (yd 1.89 @ 12.7 ppg). Tail w/ 200 sx Clas 88 sx cmt to reserve pits. WOC 18 hrs. Tested	e of starting any proposed work. If well is swork.)* J-55, ST&C Csg. il w/ 200 sx Class s. Test csg to 1000 psi. x BJ Lite "C" w/ 6% Gel, s "C" w/ 2% CaCl2 d BOP w/ Safety Test, Inc

Title 18 U.S C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

EM JUL 21 A 9.28

THE THE PARTY.