			· · · ·	C19	
orm 3160-5 lune 1990)	UNITED S DEPARTMENT OF BUREAU OF LAND	THE INTERIOR	811 S. 1st Street		
Do not use this form f	SUNDRY NOTICES AND for proposals to drill or t APPLICATION FOR PE	o deepen or reen	try to a different reservo	10-2834 Nivini 05055 Dir.	
SUBMIT IN TRIPLICATE 1. Type of Well Oil Oil Well Well Other 2. Name of Operator				7. If Unit or CA, Agreement Designation	
				8. Well Name and No. Fren 7 Fecleral #1	
2. Name of Operator Mewbourne Oil Company				9. API Well No.	
3. Address and Telephone No.				30-015-31264	
PO Box 5270, Hobbs, New Mexico 88241 (505-393-5905)				10. Field and Pool, or Exploratory Area North Shugart Morrow	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 990' FNL & 1980' FEL Sec. 7 T-18S R-31E				11. County or Parish, State	
				Eddy, NM	
12. CHECK API	PROPRIATE BOX(s) TO	INDICATE NATUR	RE OF NOTICE, REPORT	, OR OTHER DATA	
TYPE OF SU	TYPE OF SUBMISSION TYPE OF ACTION				
Notice of Int	ent	Abandoi	nment	Change of Plans	
و. همناح		Recomp		New Construction	
X Subsequent Report				Non-Routine Fracturing	
Final Abandonment Notice				Water Shut-Off	
		Altering Casing			
			0,000,00,00,000,00,000	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	
directionally drilled, give su	bsurface locations and measured a	nd true vertical depths for	/8" H-40 48# csg to 630'. Cet		
sks 'C' w/ 2' 8-22-00Drilled 12 1	% CaCl2. Circl 56 sks to pit. /4" hole to 4518'. Ran 9 5/8	WOC 18 hrs. Test to " J-55 & N-80 40# cs	o 1500 psi. sg to 4518'. Cemented w/ 140 ty equipment to 5000 psi. OK	00 sks Poz lite & 200 sks 'C' w/	
sks 'C' w/ 2' 8-22-00Drilled 12 1	% CaCi2. Circl 56 sks to pit. /4" hole to 4518'. Ran 9 5/8 Circl 140 sks to pit. WOC 18	WOC 18 hrs. Test to " J-55 & N-80 40# cs 3 hrs. Test w/ 3rd par	g to 4518'. Cemented w/ 140	00 sks Poz lite & 200 sks 'C' w/	
sks 'C' w/ 2' 8-22-00Drilled 12 1 2% CaCl2.	% CaCi2. Circl 56 sks to pit. /4" hole to 4518'. Ran 9 5/8 Circl 140 sks to pit. WOC 18	WOC 18 hrs. Test to " J-55 & N-80 40# cs 3 hrs. Test w/ 3rd par	g to 4518'. Cemented w/ 140 ty equipment to 5000 psi. OK	00 sks Poz lite & 200 sks 'C' w/	

-