

POGO PRODUCING COMPANY
SHUGART " 6" FEDERAL # 1
UNIT "H" SECTION 6
T18S-R31E EDDY CO. NM

In response to questions asked under Section II B of Bulletin NTL-6 the following information is provided for your consideration:

1. Location: 1810' FNL & 380' FEL SEC. 6 T18S-R31E EDDY CO. NM.
2. Elevation above sea level:
3. Geologic name of surface formation: Quaternary Aeolian Deposits.
4. Drilling tools and associated equipment: Conventional rotary drilling rig using fluid as a circulating medium for solids removal.
5. Proposed drilling depth: 12,500'
6. Estimated tops of geological markers:

Rustler Shhydrite	475'	Atoka	10,800'
San Andres	4410'	Morrow	11,300'
Wolfcamp	9350'	Barnett	11,900'
Strawn	10,570	Mississippian	12,100'
7. Possible mineral bearing formation:

San Andres	Oil	Atoka	Gas
Wolfcamp	Oil	Morrow	Gas
Strawn	Gas	Mississippian	Gas
8. Casing program:

Hole size	Interval	Casing OD	Weight	Thread	Collar	Grade
25"	0-40'	20"	NA	NA	NA	Conductor
17½"	0-500'	13 3/8"	48	8-R	ST&C	H-40
12¼"	0-4500'	8 5/8"	32 & 24	8-R	ST&C	J-55
7 7/8"	0-12,500'	5½"	20 & 17	8-R	LT&C	N-80