Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

cist

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

Expires: March 31, 1993

5. Lease Designation and Serial No.

NM	010907A

SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well 8. Well Name and No. Other Well Well Sand Dunes 35 Federal Com #1 2. Name of Operator 9. API Well No. Mewbourne Cil Company 30-015-31395 3. Address and Telephone No. 10. Field and Pool, or Exploratory Area PO Box 5270 Hobbs, New Mexico 88241. 505-393-5905 N. Turkey Track Morrow 4. Location of Well Footage, Sec., T., R., M., or Survey Description) 11. County or Parish, State 1650' FSL & 990' FEL Sec.35 T-18S R-29E UNIT J Eddy, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF ACTION TYPE OF SUBMISSION Abandonment Change of Plans Notice of Intent **New Construction** Recompletion Non-Routine Fracturing Subsequent Report Plugging Back Water Shut-Off Casing Repair Altering Casing Conversion to Injection Final Abandonment Notice 🔀 Other _Spud, Surf & Inter Csa Dispose Water (Note: Report results of multiple completion on Wel Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinet details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markders and zones pertinent to this work.)* 12/06/00...Spud 17 1/2" hole @ 3:30 pm. TD'ed hole @ 404'. Lost returns @ 75'. Ran 13 3/8" 48# H-40 csg to 404'. Cemented w/ 200 sks Thicksad, mixed @ 14.6 #/g & 1.51 yd; 162 sks BJ Lite 'C' w/ additives, mixed @ 12.4 #/g & 1.99 yd. Tailed w/ 200 sks 'C' w/ 2% CaCl2. Mixed @ 14.8 #/g & 1.32 yd. WOC 6 hrs. RIH w/ 1" tbg & tagged @ 170'. Ran 14 plugs, 25-50 sks per plug, using a total of 425 sks 'C' w/ 3-5% CaCl2. Tagged TOC on the 14th plug @ 68'. As per Jim Amos (BLM), ready mixed to surface. WOC 38 Hrs. Test BOP to 500 psi. OK. 12/15/00...TD'ed 12 1/4" hole @ 3225'. Ran 8 5/8" 32# J-55 casing to 3225'. Cemented w/ 1100 sks BJ Lite 'C' w/ additives. Mixed @ 12.7 #/g & 1.93 yd. Tailed w/ 200 sks 2% CaCi2. Mixed @ 14.8 #/g & 1.34 yd. Circl 158 sks to pit. Test Bop to 2000 psi. OK. ្ត: 68 14. I hereby certify that the foregoing is true and correct NM Young District Manager 12/26/00 State office use) (This space for Approved by _____Conditions of approval, if any: Title

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.