

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

C/S R
FORM APPROVED
Bureau No. 1004-0135
Expires: March 31, 1993
Lease Designation and Serial No. 105206
N.M. Oil Cons. Division
811 S. 1st Street
Artesia, NM 88210-2834
6. If Indian, Allottee or Tribe Name

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT-" for such proposals

SUBMIT IN TRIPLICATE

CONFIDENTIAL

1. Type of Well
Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator
Nearburg Producing Company

3. Address and Telephone No.
3300 North A Street, Building 2, Suite 120, Midland, Texas 79705 (915) 686-8285

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
Unit N, 660' FSL and 1850' FWL, Section 33, T18S, R27E

7. If Unit or CA, Agreement Designation
8. Well Name and No.
Kaiser Lake 33 Federal #1
9. API Well No.
30-015-31616
10. Field and Pool, or Exploratory Area
Undes, Lake East, Morrow (Gas)
11. County or Parish, State
Eddy County, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

04/04/01-04/08/01: Drilled 7-7/8" hole to 10,000. Plug back to 6400'. Pump 1st plug f/9350' to 9202' w/55 sx "H" cmt. Pump 2nd plug f/7450' to 7300' w/55 sx "H" cmt. Pump plug back, plug f/6350' to 5850' w/90 sx "H" cmt. Pull 10 stds. WOC. Set 50,000# on plug. Run DST. Prepare to plug and abandon as follows:

- 1.) Set 1st plug f/5000' to 4900' w/40 sx.
2.) Set 2nd plug f/2370' to 2270' w/40 sx. Tag plug @ 2390'.
3.) Set 3rd plug f/2390' to 2350' w/40 sx.
4.) Set 4th plug f/1100' to 1000' w/ 40 sx.
5.) Set 5th plug f/50' to surface w/20 sx.
6.) Jet pits, weld on cap and set dry hole marker.
7.) Release rig at 2400 hrs on 04/08/01.

Well Plugged 04/08/2001

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed Kim Stewart

Title Regulatory Analyst

Date 04/25/01

(This space for Federal or State office use)

(ORIG. SGD.) DAVID R. GLASS

Approved by
Conditions of approval, if any:

Title PETROLEUM ENGINEER

Date

MAY 09 2001

RECEIVED

2001 MAY -2 AM 10:24

RECEIVED
FBI - NEW YORK