

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-163
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-015-31649

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
V-5867

7. Lease Name or Unit Agreement Name
Tumbledink AVK State Com

8. Well No.
2

9. Pool name or Wildcat
Richard Knob Atoka Morrow

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3543' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter P : 660 Feet From The South Line and 660 Feet From The East Line
Section 16 Township 18S Range 25E NMPM Eddy County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Production casing and cement <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 8930'. Reached TD at 10:00 PM 5-22-2001. Ran 211 joints of 5-1/2" 17# casing as follows: 25 joints of 5-1/2" 17# N-80 sandblasted (1009.58') and 186 joints of 5-1/2" 17# L-80 varnished (7917.81') of casing set at 8930'. Float shoe set at 8930'. Float collar set at 8886'. Bottom marker set at 8612'. Top marker set at 7918'. Pumped 150 bbls mud with 150 scf/bbl N2 ahead of 900 sacks "C" (65-35), 5# LCM, 1/4#/sack celloflake and 4/10% FL52 (yield 2.00, weight 12.4). Tailed in with 325 sacks Poz C (yield 1.60, weight 13.2). PD 9:30 PM 5-25-2001. Bumped plug to 2120 psi for 2 minutes, OK. WOC. Released rig at 4:45 AM 5-25-2001.

Waiting on completion unit.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE June 30, 2001
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR

NOV 13 2001

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: