

DRILLING PROGRAM

EOG RESOURCES, INC.
Oreo " 25" Federal Com No. 1
1,575' FEL & 1,920' FSL
SEC. 25, T18S, R29E
EDDY COUNTY, NM

1. GEOLOGIC NAME OF SURFACE FORMATION:

Permian

2. ESTIMATED TOPS OF IMPORTANT GEOLOGICAL MARKERS:

Yates	975'
Queen	1,825'
Bone Springs	3,900'
Wolfcamp	9,050'
Strawn	10,375'
Atoka	10,625'
Morrow	10,900'

3. ESTIMATED DEPTHS OF ANTICIPATED FRESH WATER, OIL OR GAS:

Upper Permian Sands	Above 250'	Fresh Water
Strawn	10375'	Oil
Atoka	10900'	Gas

4. CASING PROGRAM

Hole Size	Interval	OD Casing	Weight Grade Jt. Cond. Type
14 3/4"	0-450'	11 3/4"	42# H-40 ST&C WITNESS
11"	0-3500'	8 5/8"	32# J-55 LT&C
7 7/8"	0-11000'	5 1/2"	17# S95/P110 LT&C

Cementing Program:

11 3/4" Surface Casing:	Cement to surface with 200 sx Prem Plus, 3% Econolite, 25 Calcium Chloride, 0.25#/sx Flocele, 150 sx Prem Plus, 2% Calcium Chloride
8 5/8" Intermediate:	Cement to surface with 800 sx Interfill C, .25#/sx flocele, 250 sx Premium Plus, 2% Calcium Chloride
5 1/2" Production:	Cement w/930 sx Premium, 3% Econolite, 5#/sx Salt (3%), 0.2% HR5, .25#/sk Flocele, 250 sx Prem 50/50 Poz mix 'A', 2% Halliburton-Gel First 2%, 0.5% Halad-322. This is designed to bring TOC to 4500'.