INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southea	stern New Mexico	Northwestern New Mexico			
T. Anhy 470	T. Canyon	T. Ojo Alamo			
T. Salt	T. Strawn 10,805	T. Kirtland-Fruitland	T. Penn. "C"		
B. Salt	T. Atoka 11,095	T. Pictured Cliffs	T. Penn, "D"		
T. Yates 1,940	T. Miss11,858	T. Cliff House	T. Leadville		
T. 7 Rivers 2,230	T. Devonian	T. Menefee	T. Madison		
T. Queen 2,865			T. Elbert		
T. Grayburg 3,185	T. Montoya	T. Mancos	T. McCracken		
T. San Andres 3,690	T. Simpson	T. Gallup	T. Ignacio Otzte		
T. Glorieta	T. McKee	Base Greenhorn	T. Granite		
T. Paddock	T. Ellenburger	_ T. Dakota	T		
T. Blinebry	T. Gr. Wash	T. Morrison	T		
T.Tubb	T. Delaware Sand	T.Todilto	T		
T. Drinkard	T. Bone Springs5,275	T. Entrada	T		
T. Abo	T. Bone Springs 1 st 6,960	T. Wingate	T		
T. Wolfcamp 8,720	TBone Springs 2 nd 7,395	T. Chinle	T		
T. Penn 9,940	T. Bone Springs 3 rd 8,535	T. Permian	T		
T. Cisco (Bough C)	T. Morrow Clastics 11,550	T. Penn "A"	T		
			OIL OR GAS SANDS OR ZONES		
No. 1, from 11,810	to11,828	No. 3, from	to		
	to	No. 4, from	to		
		WATER SANDS			
Include data on rate of wat	ter inflow and elevation to which wa	ter rose in hole.			
No. 1. from	to	feet			

No. 1. fro	om	to	feet
		to	-
,		to	
110. J, III	VIII	•••••••••••••••••••••••••••••••••••••••	

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	То	Thickness In Feet	Lithology	ſ	From	То	Thickness In Fect	Lithology
0	470	470	Red Beds & Aluvium	Γ				
470	1940	1470	Salt & Anhydrite					
1940	3185	1245	Anhydrite, Dolomite & Sand					
3185	3690	505	Dolomite & Sand					
3690	5275	1585	Dolomite					
5275	6910	1635	Limestone					
6910	8720	1810	Dolomite & Sand					
8720	9940	1220	Dolomite, Limestone & Shale					
9940	10805	865	Shale & Limestone					
10805	11095	290	Limestone & Shale					
11095	TD	855	Limestone, Shale & Sand					
	(11950)							
						l		
		1						
	1	I	1	I I		1	1	1