Submit 3 Copies To Appropriate District Office	State of No			\	Form C-103
District I	Energy, Minerals and Natural Resources			WELL API NO.	Revised March 25, 1999
1620 N. French Dr., Hobbs, NM 88240 District II					•
811 South First, Artesia, NM 88210	OIL CONSERVATION DIVISION			30-015-31969 5. Indicate Type of	of Lease
District III 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. Francis Dr.			STATE T	
District IV	Santa Fe, NM 87505			6. State Oil & G	
1220 S. St. Francis Dr., Santa Fe, NM 87505				VO-5071	
SUNDRY NOTICES AND REPORTS ON WELLS				7. Lease Name or	Unit Agreement Name:
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG-BACK TO A					
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-10) FOR SUCH PROPOSALS.)				Bonanza AZQ State Com	
1. Type of Well:					
Oil Well Gas Well X	Other \(\sqrt{\chi_0}		<u> </u>		
2. Name of Operator	m	00 12	1. 2 3	8. Well No.	
rates Petroleum Corporation 3/11					
3. Address of Operator				9. Pool name or Wildcat Wildcat Chester	
105 S. 4 th Street Artesi	a, NM 88210		~ A3/	Wildcai Cheste	? 1
4. Well Location				<u>. </u>	
4. Well Education					
Unit Letter P: 660 feet from the South line and 660 feet from the East line					
Section 17	Township 18S	Range	25E	NMPM Edo	ly County
en de la companya de La companya de la co	10. Elevation (Show who	ether Di	R, RKB, RT, GR, etc		
3569' GR					
11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data					
NOTICE OF IN	TENTION TO:		SUB	SEQUENT REI	PORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON	PLUG AND ABANDON REMEDIAL WORK ALTERING CASING			
TEMPORARILY ABANDON	CHANGE PLANS	S COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT			
PULL OR ALTER CASING	MULTIPLE COMPLETION		CASING TEST AND CEMENT JOB		
OTHER:			OTHER: Set production casing		
Describe proposed or completed op					
starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.					
0.17/00 5	1 / 00 0) / 0 / 5 / 5				
8/7/02 - Reached TD of 8800'					
56 joints SB (2491.13'), 144 joints varn (6326.58'). Float shoe set at 8800'. Float collar set at 8756'. Bottom marker set at 7029'. Cemented with 150 SCF nitrogen/150 bbls of mud ahead of 975 sx BJ Lite "C" Poz with additives.					
Tailed in with 900 sx Super "C" Modified with additives. PD at 2:45 PM. Cement top within 500' of surface					
according to differential pressure. Centralizers 1, 3, 5, 8, 11, 14, 17, 20, 23, 26, 29, 32, 35, 38 and 41. Rig released					
at 7:00 PM.					-
I hereby certify that the information	above is true and complet	e to the	best of my knowled	ge and belief.	
SIGNATURE Lina, Hu	enta, TITLE R	eaulat	on/Compliance	Supervisor DATI	E <u>August 13, 2002</u>
Type or print name Ting Huerl		<u>cgolal</u>	OLA COLLIBIIOLICE		6. 505-748-1471
(This space for State use)	<u> </u>			rerephone iv	5. 500 / HO 1 H/ 1
(This space for State user)	HOWAL SIGNED BY TH	w w. c	NU		NIC 4 9 2
	STRICT II SUPERVISOR				DATE NIS 1 9 2