

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO. 30-015-32009
Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
State Oil & Gas Lease No. E-1821
Lease Name or Unit Agreement Name Illinois Camp 17 State Com
Well No. 3
Pool name or Wildcat Illinois Camp Morror, North

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	
Name of Operator Mewbourne Oil Company	
Address of Operator PO Box 5270, Hobbs, New Mexico 88241	
Well Location Unit Letter <u>M</u> : <u>870</u> Feet From The <u>South</u> Line and <u>660</u> Feet From The <u>West</u> Line Section <u>17</u> Township <u>18S</u> Range <u>28E</u> NMPM <u>Eddy</u> County	
Elevation (Show whether DF, RKB, RT, GR, etc.) 3607' GL	

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐


SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ANBANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

10/15/01...Spud well. TD'ed 17 1/2" hole @ 410'. Ran 410' 13 3/8" 48# H-40 csg. Cemented w/ 160 sks BJ Lite/C w/ additives. Mixed @ 12.4 #/g & 2.0 yd. Tailed w/ 200 sks C w/ 2% CaCl2. Mixed @ 14.8 #/g & 1.34 yd. Circl 43 sks to pit. WOC 18 hrs. Tested csg to 1000 psi. OK. Drilled 12 1/4" hole.

10/27/01...TD'ed 12 1/4" hole @ 4410'. Ran 4410' 40# J-55 & N-80 csg. Cemented w/ 1100 sks BJ Lite/C w/ additives. Mixed @ 12.4 #/g & 2.09 yd. Tailed w/ 200 sks C w/ 2% CaCl2. Mixed @ 14.8 #/g & 1.34 yd. Circl 110 sks to pit. WOC 18 hrs. Tested csg & BOP to 2500 psi. OK. Drilled 8 3/4" hole.



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE N.M. Young TITLE District Manager DATE 10-29-01

TYPE OR PRINT NAME N.M. Young TELEPHONE NO. 505-393-5905

(This space for State Use)

APPROVED BY Jim W. Burns TITLE SUPERVISOR, DISTRICT II DATE NOV 05 2001

CONDITIONS OF APPROVAL, IF ANY: