Form 3160-5 (August 1999)

or fraudulent statements or representations as to any matter within its jurisdiction

DEPART IT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

Oil Cons. N.M. /-Dist. 2 FORW APPROVED OMB No. 1004-0135

1301 W. Grand Avenueres November 30, 2000 Artesia, NM 382 Orial No.

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals

LC-028990-B

6. If Indian, Allottee or Tribe Name

at	Januoned Well. Use roll	11 3100-3 (Al D) 101 300	in proposais.	0.17 (1.0.0.1.7.7 (1.0.0.0.0.0.0.0.1.1.1.0.0.0.0.0.0.1		
				N/A		
				7. If Unit or CA/Agreement	, Name and/or No.	
SUBMIT	IN TRIPLICATE - O	ther Instructions o	on reverse side	N/A		
Type of Well			12345	8. Well Name and No.		
X Oil Well Gas Well Other			123456706	Creek AL Federal #	reek AL Federal #15	
2. Name of Operator	/		 ★	9. API Well No.		
Yates Petroleum Co	orporation		- /83 · · · · · · · · · · · ·			
3a Address		3b. Phone No. (includ	12° 12°	10. Field and Pool, or Explo	oratory Area	
105 S. 4th Street - A		505-748-1471	103 ADIA	_ ਲੋ - ਨੋ / Shugart Bone Sprin	nae	
4 Location of Well (Footage, Sec., T.,R., M., or Survey Description) 1980' FNL and 990' FEL				11. County or Parish. State		
Section 24 T18S-R30E			\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \	§/ ,		
3ection 24 1 103-130E			18020897	Eddy County, New	Mexico	
12. CHECK A	PPROPRIATE BOX(ES	S) TO INDICATE NAT	URE OF NOTICE, REPORT			
TYPE OF SUMISSION			TYPE OF ACTION			
Notice of Intent	Acidize	Deepen	Production (Start/Resume)	Water Shut-Off		
X Subsequent Report	Alter Casing	Fracture Treat	Reclamation	Well Integrity		
Final Abandonment Notice	Casing Repair	New Construction	Recomplete	Set production casing		
	Change Plans	Plug and Abandon	Temporarily Abandon			
	Convert to Injection	Plug Back	Water Disposal			
completion or recompletion in a nereclamation, have been completed 12/23/01 - Tested BOP to 1/2/02 - Reached TD at 8 1/3/02 - Ran 200 joints (8 25 joints 5-1/2" 17# J-55 157 joints 5-1/2" 15.5# Float shoe set at 8405'. Cemented with 200 sxs 5 1/4/02 - PD at 5:45 AM. Stage 2 - Pumped 600 sx	ew interval, a Form 3160-4 shall bid, and the operator has determined 3000# witnessed by Gen 405' at 1:30 AM. Run operator has been 405' at 1:30 AM. Bumped plug to 1:300 AM. Bumped plug to 1:00 AM. Bumped plug to 1:300 AM.	e filed once testing has been conditional inside. Hunt with Carlsbad BLen hole logs. Logger's Tis' as follows: D'. DV tool set at 6982.4 with .5% FL52 + .5% Fl for 1 min, held OK. 5 pps gilsonite + 1/4 pps	.M. D 8411'. 15 joints 5-1/2" 17# J-55 3 joints 5-1/2" 17# J-55 1'. Bottom marker set at 7509.7 .25 + 8 pps gilsonite + 3% KCI (s celloflake (yld 1.95, wt 12.5).	Varn (629.04') /arn (124.65') /5'. yld 1.61; wt 13.2). ACCEPTED Fo	uding	
Name (Printed Typed) Susan Herpin Signature			Title Engineering Techn Date 20-Mar-02		SYAK , FHG'S SEB	
	THIS	SPACE FOR FEDE	RAL OR STATE OFFICE			
Approved by			Title	Date		
the applicant holds legal or equita applicant to conduct operations the		ect lease which would entitle the	Office			
Title 18 U.S.C. Section 1001 and	Title 43 U.S.C. Section 1212, mak	e it a crime for any person know	ingly and willfully to make to any departme	nt or agency of the United States any fa	ise, fictitious	