N. W. SUBMIT IN TRIPLICATES

PORA	ijΑJ	PRC)VE	D
OMB	NO.	100	1-01	36
REMINAL:	Febr	TATY	28.	199

DEI		TES:			Expires: Februar	y 25, 1995 \	
	PARTMENT OF TH	IE INTERIO		1. 12 Last 1	G. LANS DESCRIPTION A		
	BUREAU OF LAND MA	NAGEMENT	- Ariesia, I	11. (L	NM 93771 out of	fNM 025503	
ADDI IOATI	ON FOR PERMIT 1	O DRILL			6. IF INDIAN, ALLOTTES	OR TRIBE NAME	
	JN FUN FERMIT	O 5111EE	<u> </u>		NA NA		
DRILL X	DEEPI	EN 🗆			7. UNIT AGREEMENT NA	19119	
TYPE OF WELL		AIRG	LE TO MOLTER		pending	2112	
MELL X MELL C	OTEN	BOM		<u> </u>	Shugart West "24"		
HAME OF OPERATOR KCS M	edallion Resources, Ir	nc. 16	1859	-	9. API WELL NO.	`	
ALLERING AND THE SPHONE NO.	,	10	1001		30-015-	32130	
7130 South Lewis Ave	enue, Suite 700, Tulsa, Ok	ζ 74136-54 8 9.	Phone (918)499-13	325	10. FIBLD AND POOL, O	_	
ACATION OF WELL (Report location					Shugart	Bono Spring	
At surface 370 ft FNL & 1700 ft FEL of Section 24					11. SEC., T., R., M., OR BUE. AND SURVEY OR ARRA		
At proposed prod. some					Sec. 24, T18S, R30E N.M.P.M.		
	Same Un	11 13			12. COUNTY OR PARISH 13. STATE		
DISTANCE IN MILES AND DIRECT	cation is about 7 miles SE of Lo	ne Post Offics*			Eddy	New Mexico	
	ALION IS ADOUL / HIRES SE OF LC		OF ACRES IN LEASE	 17, NO. Ω	F ACESS ASSIGNED		
DISTANCE FROM PROPUSED* LOCATION TO NEARBET	370 ft	i	cres more or less		40 Acres		
PROPERTY ON LEASE LINE, FT. (Also to nearest drig, unit its			OSED DEPTH	20. BOTAL	Y OR CABLE TOOLS		
DISTANCE FROM PROPOSED LOC TO MEAREST WELL, DRILLING.	COMPLETED, 943 ft		8,500 ft		Rotary Tools		
OR APPLIED FOR, ON THIS LEASE, BLEVATIONS (Show whether DF,				<u> </u>	22. APPROX. DATE WO		
BUSYATIONS (CHOW WHENEX DI)	3640 ft, G	round Level			15 October 2	001	
Secretary's Potasi	PROPOSEI	CASING AND	CEMENTING PROGRA	M			
		PER FOOT	SETTING DEPTH	Can	Capitan, Southower Master Basin		
	L 12001 CENTO	73 lbs.	40 to80 ft	F	Ready-Mix to surface		
17 1/2" H40	10, 20		760 ft		520 sacks w/additives		
11" J55	8 5/8" 32	lbs.	2,800 ft		80 sacks w/additives		
7 7/8" J55	, 5 1/2" 1 15	5 & 17 lbs.	8,500 ft		180 sacks w/additives		
1							
Drill 26 in hole and set 20 in corocdure: 1. Drill 26 in hole and set 20 in corocdure: 2. Drill 17 1/2 in hole to 760 ft and sorocdure: 3. Drill 11 in hole to 2800 ft and sorocdure: 5. Drill 27/8 in hole through the Borocdure: 6. Drill 7 7/8 in hole through the Borocdure: 7. Run electric logs. Shoot sideward: 8. If warranted, run and cement 5 in slurry to fill 500 ft into the 8 5/8 in 19. Test 5 1/2 in casing to 3000 psignations. A. Location and elevation plat. B. Location Verification Map. C. Vicinity map.	I set 13 3/8 in casing. Cement to at 8 5/8 in casing. Cement to sure to 2750 psig. 20 ft of shoe. Test casing to 15 tone Springs formation to TD. It cores if desired. I/2 in casing w/stage collar at 4. " surface casing	to surface. Inface. 100 psig. DST as necessary 300 ft. Cement to G. H. I		Area	I through stage collar with	sufficient NS67897077	

(This space for Federal or State office use) Application approval does not warrant or certify that the applicant holds logal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations

CONDITIONS OF APPROVAL, IF ANY:

ASSOC. STATE DIRECTOR DATE DEC 0 4 2001

ISI RICHARD A. WHITLEY

*See Instructions On Reverse Side APPROVAL FOR 1 YEAR

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any agree within its jurisdiction.

A PROVAL SUBJECT TO **GENERAL REQUIREMENTS AND** SPECIAL STIPULATIONS **ATTACHED**