

DRILLING PROGRAM

EOG RESOURCES, INC.
Peanut Butter "13" Fed. Com. No.1
Sec. 13 T18-S; R29-E
Eddy County NM

1. GEOLOGIC NAME OF SURFACE FORMATION:

Permian

2. ESTIMATED TOPS OF IMPORTANT GEOLOGICAL MARKERS:

Yates	975'
Queen	1600'
Bone Springs	4000'
Wolfcamp	9000'
Strawn	10325'
Atoka	10625'
Morrow	11125'

3. ESTIMATED DEPTHS OF ANTICIPATED FRESH WATER, OIL OR GAS:

Upper Permian Sands	Above 250'	Fresh Water
Strawn	10325'	Oil
Atoka	10625'	Gas
Morrow	11125'	Gas

4. CASING PROGRAM

Hole Size	Interval	OD Casing	Weight Grade Jt. Cond. Type
14 3/4"	0-450'	11 3/4"	42# H-40 ST&C
11"	0-3500'	8 5/8"	32# J-55 LT&C
7 7/8"	0-11200'	5 1/2"	17#S95/P110 LTC

Cementing Program:

11 3/4" Surface Casing: Cement to surface with 200 sx Prem Plus, 3% Econolite, 25 Calcium Chloride, 0.25#/sx Flocele, 150 sx Prem Plus, 2% Calcium Chloride

8 5/8" Intermediate: Cement to surface with 800 sx Interfill C, .25#/sx flocele, 250 sx Premium Plus, 2% Calcium Chloride

5 1/2" Production: Cement w/930 sx Premium, 3% Econolite, 5#/sx Salt (3%), 0.2% HR5, .25#/sk Flocele, 250 sx Prem 50/50 Poz mix 'A', 2% Halliburton-Gel First 2%, 0.5% Halad-322. This is designed to bring TOC to 4500'.