

04/08/2002 18:16 5053903065

SZENASY

PAGE 03

Computalog Drilling Services

Client : EOG Resources
 Well : Oatmeal 8 Fed. Com. #1
 Location : Eddy County, New Mexico
 License :
 Comment : Grid North

UWI #:

Page: 1
 Date: 5/25/2002
 File : 08FC1

Vertical Section Calculated Along Azimuth 180.00°
 KB Elevation = 0.00ft GR. Elevation = 3509.00ft

MD ft	Inc deg	Azi deg	TVD ft	North ft	East ft	V'Sect ft	D'Leg °/100	Build °/100	Turn °/100
9434.00	1.02	265.10	9433.00	-37.36	-18.21	37.36	0.00	0.00	0.00
9486.00	1.20	224.10	9484.99	-37.79	-19.05	37.79	1.53	0.35	-78.85
9549.00	2.90	198.50	9547.95	-39.78	-20.01	39.78	3.00	2.70	-40.83
9612.00	3.00	196.90	9610.87	-42.86	-21.00	42.86	0.21	0.16	-2.54
9676.00	3.90	183.00	9674.75	-46.64	-21.80	46.64	1.91	1.41	-21.72
9740.00	4.10	178.50	9738.59	-51.10	-21.85	51.10	0.58	0.31	-7.03
9803.00	4.40	178.00	9801.42	-55.76	-21.43	55.76	0.58	0.48	-3.97
9868.00	4.80	173.50	9864.22	-60.79	-20.96	60.79	0.71	0.63	-3.97
9930.00	5.80	167.00	9927.84	-66.60	-19.93	66.60	1.82	1.56	-10.16
9993.00	6.10	168.20	9990.61	-72.98	-18.53	72.98	0.52	0.48	1.90
10057.00	5.80	171.60	10054.26	-79.51	-17.36	79.51	0.72	-0.47	5.31
10121.00	5.50	174.80	10117.95	-85.76	-16.61	85.76	0.68	-0.47	5.00
10185.00	6.10	168.00	10181.62	-92.15	-15.63	92.15	1.42	0.94	-10.63
10249.00	5.40	171.40	10245.30	-98.45	-14.47	98.45	1.22	-1.09	5.31
10314.00	5.50	167.50	10310.01	-104.51	-13.34	104.51	0.59	0.15	-6.00
10378.00	5.30	168.30	10373.72	-110.40	-12.07	110.40	0.33	-0.31	1.25
10442.00	5.80	175.10	10437.42	-116.52	-11.20	116.52	1.29	0.78	10.62
10506.00	6.40	169.00	10501.08	-123.24	-10.24	123.24	1.38	0.94	-9.53
10569.00	6.30	171.50	10563.67	-130.11	-9.06	130.11	0.47	-0.16	3.97
10633.00	6.20	172.70	10627.29	-137.01	-8.10	137.01	0.26	-0.16	1.87
10698.00	5.30	171.60	10691.97	-143.46	-7.22	143.46	1.39	-1.38	-1.69
10761.00	5.60	176.80	10754.68	-149.41	-6.82	149.41	0.92	0.48	8.25
10826.00	5.10	177.70	10819.40	-155.46	-6.33	155.46	0.78	-0.77	1.38
10890.00	5.50	175.60	10883.13	-161.36	-5.98	161.36	0.69	0.82	-3.28
10954.00	5.40	170.00	10946.84	-167.39	-5.22	167.39	0.85	-0.16	-8.79
11018.00	5.40	169.00	11010.55	-173.31	-4.12	173.31	0.15	0.00	-1.56
11082.00	6.30	169.90	11074.22	-179.72	-2.93	179.72	1.41	1.41	1.41
11147.00	5.70	172.10	11138.86	-186.43	-1.86	186.43	0.99	-0.92	3.38
11211.00	5.50	173.80	11202.66	-192.63	-1.10	192.63	0.41	-0.31	2.66
11276.00	5.50	174.90	11267.26	-198.83	-0.48	198.83	0.16	0.00	1.69
11340.00	4.50	178.50	11331.01	-204.39	-0.14	204.39	1.64	-1.56	5.62
11404.00	4.40	182.90	11394.82	-209.35	-0.20	209.35	0.56	-0.16	6.88
11468.00	4.10	186.00	11458.64	-214.08	-0.57	214.08	0.59	-0.47	4.84
11532.00	3.40	185.30	11522.51	-218.25	-0.98	218.25	1.10	-1.09	-1.09

Bottom Hole Closure 218.25ft Along Azimuth 180.26°

BHL @ 10506 - 10569: 7595/2122W
 7525/2124W