DRILLING PROGRAM

Attached to Form 3160-3 Marbob Energy Corporation AAO Federal No. 3 330' FNL and 1690' FEL Section 1, T-18S, R-27E Eddy County, New Mexico

1. <u>Geologic Name of Surface Formation:</u>

Permian

2. Estimated Tops of Important Geologic Markers:

Permian	Surface	San Andres	1850'
Seven Rivers	450'	Glorietta	3250'
Queen	1050'		

3. Estimated Depths of Anticipated Fresh Water, Oil or Gas:

Upper Permian Sands	180'	Fresh Water
Queen	1050'	Oil
San Andres	1850'	Oil
Glorietta	3250'	Oil

No other formations are expected to give up oil, gas, or fresh water in measurable quantities. The surface fresh water sands will be protected by setting 8 5/8 casing at 350' and circulating cement back to surface. Any shallower zones above TD which contain commercial quantities of oil and/or gas will have cement circulated across them by inserting a float shoe joint into the 5 1/2" production casing which will be run at TD.

4. Casing Program:

<u>Hole Size</u>	Interval	<u>OD csg</u>	Weight, Grade, Jt. Cond. Type				
12 1/4" 7 7/8"	0 - 1320' 350' - TD	8 5/8" 5 1/2"	24# 17#		LTC NEW LTC NEW		
Cement Pro	ogram:						
8 5/8" Surface Casing:		Cemented to surface with $300sx$ of Class C w/2% cc.					
5 1/2" Production Casing:		Cemented with 750sx Class C.					